


24 x 24 mm

Illustration	Lens Colour	Lamp Voltage	Possible Contact Configuration	Part Number
--------------	-------------	--------------	--------------------------------	-------------



Illuminated Pushbutton_QXJT



Dimensional Drawing:



Cut-out Hole Drawing:



1NO 1NC Momentary/Spring Return - 24V

Red	-	-	-	1NO 1NC	GS1 QXJT-11-24-RT
Green	-	-	-	1NO 1NC	GS1 QXJT-11-24-GN
Yellow	-	-	-	1NO 1NC	GS1 QXJT-11-24-GB
Blue	-	-	-	1NO 1NC	GS1 QXJT-11-24-BL
Clear	-	-	-	1NO 1NC	GS1 QXJT-11-24-KL

2NO 2NC Momentary/Spring Return - 24V

Red	-	-	-	2NO 2NC	GS1 QXJT-22-24-RT
Green	-	-	-	2NO 2NC	GS1 QXJT-22-24-GN
Yellow	-	-	-	2NO 2NC	GS1 QXJT-22-24-GB
Blue	-	-	-	2NO 2NC	GS1 QXJT-22-24-BL
Clear	-	-	-	2NO 2NC	GS1 QXJT-22-24-KL

1NO 1NC Maintained/Latching - 24V

Red	-	-	-	1NO 1NC	GS1 QXJT-11Z-24-RT
Green	-	-	-	1NO 1NC	GS1 QXJT-11Z-24-GN
Yellow	-	-	-	1NO 1NC	GS1 QXJT-11Z-24-GB
Blue	-	-	-	1NO 1NC	GS1 QXJT-11Z-24-BL
Clear	-	-	-	1NO 1NC	GS1 QXJT-11Z-24-KL

2NO 2NC Maintained/Latching - 24V

Red	-	-	-	2NO 2NC	GS1 QXJT-22Z-24-RT
Green	-	-	-	2NO 2NC	GS1 QXJT-22Z-24-GN
Yellow	-	-	-	2NO 2NC	GS1 QXJT-22Z-24-GB
Blue	-	-	-	2NO 2NC	GS1 QXJT-22Z-24-BL
Clear	-	-	-	2NO 2NC	GS1 QXJT-22Z-24-KL


Pilot Light_QXJL5



24V

Red	24V	-	-	-	GS1 QXJL5-24-RT
Green	24V	-	-	-	GS1 QXJL5-24-GN
Yellow	24V	-	-	-	GS1 QXJL5-24-GB
Blue	24V	-	-	-	GS1 QXJL5-24-BL
Clear	24V	-	-	-	GS1 QXJL5-24-KL

Dimensional Drawing:



Cut-out Hole Drawing:




Illustration	Description	Part Number
--------------	-------------	-------------

	T5.5 LED 24V DC	<input checked="" type="checkbox"/> Red	9ML T5.5KO-R-24
		<input checked="" type="checkbox"/> Green	9ML T5.5KO-G-24
		<input checked="" type="checkbox"/> Yellow	9ML T5.5KO-Y-24
		<input checked="" type="checkbox"/> Blue	9ML T5.5KO-B-24
		<input checked="" type="checkbox"/> Clear	9ML T5.5KO-W-24

	Lead- Sealable Protective Lid - For pushbutton and jacks	<input type="checkbox"/> Transparent	GS1 KDP24 & GS1 KDQ24
		<input checked="" type="checkbox"/> Black	

	Universal Lens Remover	GS1 USK
--	-------------------------------	----------------

	Customize Nameplate w/ adhesive - For outside marking of the actuators - Text and Dimension can be customized - <i>Other colours are available: Black, Blue & etc.</i>
--	--

	Emergency Stop Nameplate w/ adhesive - For outside marking of the actuators - Cut-out hole diameter 23 x 23 mm - Text and Outer Dimension can be customized - <i>Other colours are available: White, Green, Blue, Black & etc.</i>
--	---

Technical Specification

General Data:

Front Dimensions:	27 x 27 mm
Panel Cut-out:	24 x 24 mm
Front Bezel Height:	2.5 mm
Operating Travel:	6 mm
IP Rating:	IP65
Illumination:	Yes
Contact Type:	Twin contact block. Separate plungers, positive opening contact
Protection Class:	II (protective insulation)
Connection Type:	Faston Terminal 2.8 x 0.8 mm
Contact Material:	AgNi

Max. Storage Temperature:	-50°C ... 85°C
Max. Operating Temperature:	-50°C ... 85°C, without illumination -30°C ... 65°C, using LEDs
Mechanical Life:	1 m switching cycles
Electrical Life:	1 m operations at rated load
Contact Resistance NO:	<20 mOhm
Contact Resistance NC:	<20 mOhm
Min. Current:	1 mA
Min. Voltage:	5V

	Alternate Current	Direct Current
Rated Insulation Voltage:	250V	300V
Rated Operating Voltage:	250V	250V / 125V / 60V / 24V
Rated Operating Current:	3A	0.2A / 0.4A / 1A / 2A

Approvals:



Use & Applications:

- ✓ The actuators are designed for exclusive applications, mosaic panel as well as use in harsh environments.
- ✓ Flexible contact configuration and ease of assembly.
- ✓ The units can be used in every field of application.
- ✓ The control units are designed to accept a clearly visible marking, easy to produce and comprising a variety of symbols and inscriptions.
- ✓ Multiple standards nameplates are available and also according to user's requirements.