

Barrel Power Cords

2.5mm DC Plug - DC Jack

multicomp PRO


**RoHS
Compliant**



Specifications


Connector Type A	: 2.5mm DC Power Socket
Connector Type B	: 2.5mm DC Power Plug
Withstand Voltage	: 500V/min.
Insulation Resistance	: 10MΩ/KM min.
Conductor Resistance	: 17.3Ω/KM
Test Temperature	: 20°C
Current Rating	: DC: 0.4A/300V
Operating Voltage	: 300V

Diagram



Soldered Drawing:

2.5mm DC Plug 2.5mm DC Jack



Dimensions : Millimetres

Part Number Table

Description	"L"	Part Number
Barrel Power Cord, 2.5mm DC Plug - 2.5mm DC Jack	1.5m	MP009032
	3m	MP009033
	5m	MP009034
	10m	MP009035

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp PRO