

FEATURES

- Disconnect terminal block
- Wire size of 22AWG to 12AWG
- CSA cable size of 2.5mm²
- Current rating of 12A (UL/CSA), 15A (IEC)
- Voltage rating of 600V
- Screw termination
- Single level

RS PRO, 600 V Disconnect Terminal Block, Screw Termination

RS Stock No.: 878-7584



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Looking for a way to cut off a circuit safely and efficiently? This disconnect terminal block from RS PRO uses a hinged lever, attached to a fuse, to stop the flow of electricity. Allowing you to cut off your circuit as often as you like, it's a more reliable alternative to regular fused terminal blocks, which you may need to replace more often.

General Specifications

Colour	Grey
Number of levels	Single
Termination method	Screw Down
Screw Size	M3
Rail Type Compatibility	TS35x7.5 (5.1mm x 60mm x 47.5mm), TS35x15 (5.1mm x 42.5mm x 55mm)
Contamination Degree	3
Application	Circuit boards and control panels for industrial electronics

Electrical Specifications




Current Rating	12A (UL/CSA), 15A (IEC)
Voltage Rating	600V
Rated Impulse Voltage	6kV

Mechanical Specifications


Wire size	22AWG to 12AWG
Cable CSA	2.5mm ²
Stripping Length	10mm to 12mm
Torque	4.5in-lbs
Unit Weight	8.9g

Approvals







Standard met	UL, CSA, IEC, ROHS Compliant, cRUus
--------------	-------------------------------------



Dimensions in mm



Product Specifications:

Specifications	2.5mm ²
Technical Data	Rated voltage / Rated current / Wire size
UL	600V / 12A / AWG 22-12
CSA	600V / 12A / AWG 22-12
IEC	500V / 15A / 0.5-2.5mm ²
Insulating impulse voltage withstand/pollution degree	6KV / 3
Torque (in -lbs)	4.5
Clamping Screw (M)	M3
Insulation stripping length (mm)	10-12 mm
Net weight per piece	8.9g
Material / Available Color (Standard Color: Beige)	 Red Orange Beige Blue Grey White Black
Rail Dimensions	T/W/H (mm)
For TS35x7.5 	5.1 x 60 x 47.5
For TS35x15 	5.1 x 60 x 55
Accessories	Cat. No.
End Bracket 	8787553 8787556
End plate 	8787540
Marking Tags 	8787590