



# **MASTER PL-C 4 Pin**

## MASTER PL-C 13W/827/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

## Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- · Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

#### **Product data**

General information		LLMF 4000 h Rated	87 %
ap base	G24Q-1 [ G24q-1]	LLMF 6000 h Rated	83 %
ife to 50% failures preheat (nom.)	13000 h	LLMF 8000 h Rated	81 %
SF preheat 2,000 hours rated	99 %		
SF preheat 4,000 hours rated	98 %	Operating and electrical	
LSF preheat 6,000 hours rated	97 %	Power (Rated) (Nom)	13.0 W
LSF preheat 8,000 hours rated	90 %	Lamp current (nom.)	0.170 A
ight technical		Temperature	
Colour Code	827 [ CCT of 2,700 K]	Design temperature (nom.)	28 °C
amp Luminous Flux 25°C EL (Nom)	925 lm		
Lamp Luminous Flux (Nom)	925 lm	Controls and dimming	
Colour Designation	Incandescent White	Dimmable	Yes
Colour Temperature, horizontal (Nom)	2700 K		
Lamp Luminous Efficacy EM (Nom)	69 lm/W	Mechanical and housing	
Colour Rendering Index,horiz (Nom)	82	Cap-base information	4P
LLMF 2000 h Rated	92 %		

## MASTER PL-C 4 Pin

Approval and application			
Mercury (Hg) content (nom.)	1.4 mg		
Energy consumption kWh/1,000 hours	15 kWh		
Product data			
Full product code	871150062326300		

8711500623263


MASTER PL-C 13W/827/4P 1CT/5X10BOX

Order code	927907182701		
SAP numerator – quantity per pack	1		
Numerator – packs per outer box	50		
SAP material	927907182701		
Net Weight (Piece)	49.900 g		
ILCOS code	FSQ-13/27/1B-E-G24q=1		

## Dimensional drawing


Order product name

EAN/UPC - product




MASTER PL-C 13W/827/4P 1CT/5X10BOX

#### Photometric data



LDPB\_PLC4P\_827-Spectral power distribution B/W


Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/827/4P	27.1 mm	27.1 mm	97.5 mm	117.0 mm	131.9 mm
1CT/5X10BOX					



LDPO\_PLC4P\_827-Spectral power distribution Colour

## MASTER PL-C 4 Pin

## Lifetime





1

LDLE\_PLC4P\_0002-Life expectancy diagram

LDLM\_PLC4P\_0001-Lumen maintenance diagram



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 6 - data subject to change