

Product data sheet

Specifications



Shunt trip release MX, ComPacT NSX, 48VAC 50/60Hz, screwless spring terminal connections

LV429385

Main

Range	ComPacT
Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	ComPacT NSX new generation ComPacT NSX DC new generation ComPacT NSX ComPacT NSX DC EasyPact CVS PowerPact Multistandard
Voltage release type	Opening coil Shunt trip release
[Uc] control circuit voltage	48 V AC 50/60 Hz

Complementary

Operating threshold	0.7...1.1 x Un opening
Response time	50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Supply inrush power	10 VA
Auxiliary connection terminal	Spring 0.5...1.5 mm ² (AWG 20...AWG 16)
Wire stripping length	7 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	112 g
Package 1 Height	4.5 cm
Package 1 width	4.6 cm
Package 1 Length	6.2 cm
Unit Type of Package 2	S03
Number of Units in Package 2	60

Package 2 Weight	7.49 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Package 3 Height	30.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------