# Product data sheet **Characteristics**

# **AR112SH6**

APC NetShelter 12U Wallmount Rack Enclosure Cabinet Single Hinged Server Depth







#### Overview Presentation

Ideal for retail, healthcare, and educational facilities, this wall mount rack offers an efficient solution for deploying server and networking equipment for edge computing applications. This rack enclosure is wall mountable, ideal for areas with limited floor space, and is designed specifically for servers and network switches and patch panels. The cabinet's door is reversible and is compatible with APC's Netbotx security upgrade to provide remote access, video surveillance, and environmental monitoring (sold separately). Optional 120V fan tray can be top or bottom mounted (sold separately) Both the top and bottom feature knockouts of 1/2U mounting space for accessories. And several APC Smart-UPS models low-profile provide easy UPS integration and mounting 12U Wall mount cabinet, mounting depth range of 2.87 to 20.8 inches, 200lb weight capacity, 19"" rack width, ships fully assembled, ventilated with accessory integration options, 5 year APC warranty.
Usually in Stock

Lead time

#### Main

Product or component type	Rack enclosure
Number of rack unit	12U

#### **Physical**

Height62 cmWidth60 cmDepth60 cmNet weight19.19 kgColourBlackMounting supportWallMounting preferenceNo preferenceMounting modeNot rack-mountableMaximum mounting depth52.83 cmMinimum mounting depth7.29 cmRack width19"Permanent permissible load90.72 kg static	i nyoloal	
Depth60 cmNet weight19.19 kgColourBlackMounting supportWallMounting preferenceNo preferenceMounting modeNot rack-mountableMaximum mounting depth52.83 cmMinimum mounting depth7.29 cmRack width19"	Height	62 cm
Net weight19.19 kgColourBlackMounting supportWallMounting preferenceNo preferenceMounting modeNot rack-mountableMaximum mounting depth52.83 cmMinimum mounting depth7.29 cmRack width19"	Width	60 cm
ColourBlackMounting supportWallMounting preferenceNo preferenceMounting modeNot rack-mountableMaximum mounting depth52.83 cmMinimum mounting depth7.29 cmRack width19"	Depth	60 cm
Mounting supportWallMounting preferenceNo preferenceMounting modeNot rack-mountableMaximum mounting depth52.83 cmMinimum mounting depth7.29 cmRack width19"	Net weight	19.19 kg
Mounting preference No preference   Mounting mode Not rack-mountable   Maximum mounting depth 52.83 cm   Minimum mounting depth 7.29 cm   Rack width 19"	Colour	Black
Mounting modeNot rack-mountableMaximum mounting depth52.83 cmMinimum mounting depth7.29 cmRack width19"	Mounting support	Wall
Maximum mounting depth 52.83 cm   Minimum mounting depth 7.29 cm   Rack width 19"	Mounting preference	No preference
Minimum mounting depth 7.29 cm   Rack width 19"	Mounting mode	Not rack-mountable
Rack width 19"	Maximum mounting depth	52.83 cm
	Minimum mounting depth	7.29 cm
Permanent permissible load 90.72 kg static	Rack width	19"
· · · · · · · · · · · · · · · · · · ·	Permanent permissible load	90.72 kg static

### Conformance

Standards	UL 2416
	EIA-310E

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	70 cm	
Package 1 Width	68.5 cm	
Package 1 Length	68.5 cm	
Package 1 Weight	23.18 kg	



Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) CEU RoHS Declaration
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty

5 year repair or replace