



Main

Range	Acti 9
Device short name	ISW
Product or component type	Switch
Switch application	Control
Poles description	2P
Utilisation category	AC-22A

Complementary

[Ie] rated operational current	32 A 250 V AC 50/60 Hz
[Ue] rated operational voltage	415 V AC 50/60 Hz
[Ui] rated insulation voltage	250 V AC 50/60 Hz conforming to IEC EN 60669-1
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle
Local signalling	ON/OFF indication and lamp
Signalling circuit voltage	AC : 230 V 50/60 Hz
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Colour	White
Mechanical durability	300000 cycles
Electrical durability	30000 cycles
Connections - terminals	Tunnel type terminals: 1 cable(s) 1.5...10 mm ² flexible Tunnel type terminals: 1 cable(s) 1.5...10 mm ² rigid Tunnel type terminals: 2 cable(s) 2.5 mm ² flexible Tunnel type terminals: 2 cable(s) 2.5 mm ² rigid Tunnel type terminals: 2 cable(s) 4 mm ² flexible Tunnel type terminals: 2 cable(s) 4 mm ² rigid
Wire stripping length	9 mm
Tightening torque	1.2 N.m

Environment

standards	IEC EN 60669-1
IP degree of protection	IP4
pollution degree	2
tropicalisation	2

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period

18 months