

分体式液压拉马系列

Separable hydraulic gear pullers



HUANHU TOOLS



液压拉马系列 hydraulic gear pullers

技术参数 Technical parameters

型号 Model	出力 Output (T)	最大行程 Max.stroke (mm)	爪数 Claw number	张距范围 Sread (mm)	整机重量 G.W (kg)	体积 Volume (mm)
HHL-5F 配(HHB-700C)	5	50	3	50-200	15	730X180X180
HHL-10F 配(HHB-700)	10	60	3	50-250	20	730X180X180
HHL-20F 配(HHB-700)	20	70	3	100-350	27	730X210X180
HHL-30F 配(HHB-700)	30	70	3	150-400	35	730X250X180
HHL-50F 配(HHB-700)	50	60	3	200-500	55	730X250X180

功能说明 Function

- ▲利用新型液压拉马操作方便
- ▲三爪和二爪式可根据现场工作需要拆换。
- ▲爪子附三爪，高低可根据需要调整。
- ▲Simple to operate
- ▲Both z-jaw and 3-jaw styles are available.
- ▲Jaws adjustable.

整体式液压拉马系列

Hydraulic gear pullers, integral type



功能说明 Function

▲ 整体式拔轮器是一种替代传统拉马的理想化新工具。操作方便，使用省力，不受场地限制，结构紧凑，使用灵活，重量轻，体积小，携带方便，适用于工厂，维修场所。

▲ 有两钳爪或三钳爪形式可供选择。

▲ The integral pullers are compact, lightweight. Easy to carry and operate. It's least restricted by place and is extensively used by factories, repair stations, etc.

▲ Both z-jaw and 3-jaw styles are available.

技术参数 Technical parameters

型号规格 Model	HHL-5	HHL-10	HHL-20	HHL-30	HHL-50
安全负重 (T) Rated output	5	10	20	30	50
横向最长外径(mm) Max. Spread	200	250	350	400	500
最大行程(mm) Max. stroke	50	60	70	70	60
重量(kg) weight	7.5	11	19	25	45
体积(mm) Volume	(1/4)440X380X320	(1/2)440X210X360	430X400X140	480X200X180	520X250X220