



## Main

|                           |   |
|---------------------------|---|
| Product or component type | Switch  |
| Device application        | Control   |
| Load type                 | Resistive<br>Inductive<br>Incandescent lamp<br>Fluorescent lamp |
| Colour tint               | Wine gold   |

## Complementary

|                              |  |
|------------------------------|--|
| Device presentation          | Complete product   |
| Rated current                | 16 AX at 250 V AC 50/60 Hz   |
| Switch function              | 1-pole 2-way   |
| Number of gangs              | 3 gangs  |
| Number of rocker             | 3  |
| Clamping connection capacity | 3 x 2.5 mm <sup>2</sup> for solid cable(s)<br>3 x 2.5 mm <sup>2</sup> for stranded cable(s)<br>4 x 1.5 mm <sup>2</sup> for solid cable(s)<br>4 x 1.5 mm <sup>2</sup> for stranded cable(s) |
| Connections - terminals      | Brass terminal   |
| Local signalling             | Off: LED indicator, LED  |
| Material                     | Polycarbonate: grid plate<br>Polycarbonate: base<br>Polycarbonate: dolly<br>Polycarbonate: frame<br>Polycarbonate + GF 20 %: actuator  |
| Device mounting              | Surface<br>Flush   |
| Width                        | 86 mm  |
| Height                       | 86 mm  |
| Depth                        | 34.2 mm  |
| Embedding depth              | 24.5 mm  |

## Environment

|   |                       |
|---|-----------------------|
| IP degree of protection                       | IP20                  |
| Maximum ambient air temperature for operation | 35 °C                 |
| Operating altitude                            | 2000 m                |
| Relative humidity                             | 0...95 %              |
| Standards                                     | GB 16915.1<br>IS 3854 |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 3.4 cm  |
| Package 1 Width              | 8.6 cm  |
| Package 1 Length             | 8.6 cm  |
| Package 1 Weight             | 112.0 g |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |