

## **Datasheet**



## RS PRO 25m Black Hose Pipe

Stock No: 1467727

Air / Water Hose





## Codan 1225 -

Black water hose for use where a flexible, hard-wearing, weather and ozone-resistant hose is required. Peak temp. 160 C. We recommend crimp on fittings. Please contact Codan for further information.

**Type nr.** 1225

**Application:** Air / Water Hose **Standard Length:** 50 metres

Working Temperature: -30°C to 140°C

Inside: EPDM Colour: Black

Reinforcement: High Strength Synthetic Textile Yarns

Outside: EPDM Colour: Black Standards: Std. branding: -

Inside dia.	Outside	Working	Burst Pressure	Bend Radius	Weight	Product
(mm)	dia. (mm)	Pressure BAR	BAR	(mm)	(g/m)	code
19,0	27,0	20	60	105	450	1467727

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with 150 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is compiled with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose more file at ion.

environments outside the hose specification.
Please contact Codan Rubber for individual product manufacturing tolerances