



### Main

|                                    |  |
|------------------------------------|--|
| Range                              | Spacial  |
| Accessory / separate part category | Enclosure accessory  |
| Product or component type          | Door   |
| Application                        | Multi-purpose  |
| For enclosure nominal dimensions   | -  |
| Mounting location                  | Side<br>Front  |
| Range compatibility                | Spacial Spacial SF   |
| Device composition                 | 1 door<br>1 lock with handle and 5 mm double bar insert<br>1 locking bar system 4 points<br>1 reinforcement frame<br>4 hinges<br>4 locking bar catches |
| Quantity per set                   | Set of 1   |

### Complementary

|                   |                        |
|-------------------|------------------------|
| Material          | Sheet steel            |
| Colour            | Grey (RAL 7035)        |
| Surface finish    | Epoxy-polyester powder |
| Lock type         | Lock 5 mm double bar   |
| Number of locks   | 1                      |
| Door type         | External plain         |
| Door opening side | Reversible (120 °)     |
| Maximum load      | 60 kg/m <sup>2</sup>   |
| Height            | Nominal: 1800 mm       |
| Width             | Nominal: 800 mm        |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 5.0 cm   |
| Package 1 Width              | 79.0 cm  |
| Package 1 Length             | 189.0 cm |
| Package 1 Weight             | 27.0 kg  |
| Unit Type of Package 2       | P2M      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 67.0 cm  |
| Package 2 Width              | 200.0 cm |
| Package 2 Length             | 120.0 cm |
| Package 2 Weight             | 310.0 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product                                      |
| REACH Regulation           | <a href="#">REACH Declaration</a>                          |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                     |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>              |
| Circularity Profile        | No need of specific recycling operations                   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|