

LOCTITE 262

Safety Data Sheet

Page 1 of 11

SDS No.: 153483

V001.10

Revision: 05.03.2018 printing date: 16.12.2019

respiratory tract irritation

Section 1. Identification of the substance/preparation and of the company/undertaking

LOCTITE 262 Product name:

LOCTITE 262 BO 250ML EGFD Other means of identification:

IDH88396 Product code:

Recommended use of the chemical and restrictions on use

Intended use: Anaerobic Adhesive

Identification of manufacturer, importer or distributor

Importer: PT Henkel Indonesien

Jl. Tegal Rotan Raya No. 78, Bintaro - Tangerang Selatan,

Banten 15413 - Indonesia.

Tel no. +62 21 2758 6900 Fax no. +62 21 7592 4625

E-mail address of person

responsible for Safety Data

ap-ua-psra.sea@henkel.com

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call

CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

Hazard Class Hazard Category Target organ Category 2

Serious eye damage/eye irritation Specific target organ toxicity -

single exposure

Chronic hazards to the aquatic

environment

Category 3

Category 3

GHS label elements:

Hazard pictogram:



Signal word:

Warning

SDS No.: 153483 Page 2 of 11

V001.10 LOCTITE 262

Hazard statement: H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

SDS No.: 153483 Page 3 of 11

V001.10 LOCTITE 262

Section 3. Composition / information on ingredients

Substance or Mixture:

Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Ethene, homopolymer	1- 10 %	
9002-88-4		
Cumene hydroperoxide	1- 10 %	Organic peroxides E
80-15-9		H242
		Acute toxicity 4; Oral
		H302
		Acute toxicity 3; Inhalation
		H331
		Acute toxicity 4; Dermal
		H312
		Skin corrosion/irritation 1B
		H314
		Specific target organ toxicity - repeated exposure 2 H373
		Chronic hazards to the aquatic environment 2
		H411
Methyl methacrylate	0.1- 1 %	Flammable liquids 2
80-62-6		H225
		Skin corrosion/irritation 2
		H315
		Skin sensitizer 1 H317
		Specific target organ toxicity - single exposure 3
		H335
1,4-Naphthalenedione	< 0.1 %	Acute toxicity 3; Oral
130-15-4		H301
		Acute toxicity 1; Inhalation
		H330
		Skin corrosion/irritation 2; Dermal H315
		Serious eye damage/eye irritation 2A
		H319
		Skin sensitizer 1; Dermal H317
		Specific target organ toxicity - single exposure 3;
		Inhalation
		H335
		Acute hazards to the aquatic environment 1 H400
		Chronic hazards to the aquatic environment 1
		H410

Section 4. First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap.

Seek medical advice.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

SDS No.: 153483 Page 4 of 11

V001.10 LOCTITE 262

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Indication of immediate medical attention and special treatment

needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Section 6. Accidental release measures

Personal precautions: Avoid contact with skin and eyes.

Wear protective equipment.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Handling: Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

SDS No.: 153483 Page 5 of 11

V001.10 LOCTITE 262

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, INHALABLE PARTICLES 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m ³	10
	Remarks	ACGIH
Ethene, homopolymer 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m ³	10
	Remarks	ID NAB The value is for particulate matter containing no asbestos and <1% crystalline silica.
PARTICLES (INSOLUBLE OR POORLY SOLUBLE) NOT OTHERWISE SPECIFIED, RESPIRABLE PARTICLES 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m ³	3
	Remarks	ACGIH
Ethene, homopolymer 9002-88-4	Value type	Time Weighted Average (TWA):
	mg/m ³	3
	Remarks	ID NAB The value is for particulate matter containing no asbestos and <1% crystalline silica.
METHYL METHACRYLATE 80-62-6	Value type	Time Weighted Average (TWA):
	ppm	50
	Remarks	ACGIH
Methyl methacrylate 80-62-6	Value type	Time Weighted Average (TWA):
	ppm	50
	Remarks	ID NAB
METHYL METHACRYLATE 80-62-6	Value type	Short Term Exposure Limit (STEL):
	ppm	100
	Remarks	ACGIH
Methyl methacrylate 80-62-6	Value type	Short Term Exposure Limit (STEL):
	ppm	100
	Remarks	ID NAB

Respiratory protection: Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if

the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection

index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6,

corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the

gloves should be replaced.

Eye protection: Wear protective glasses.

Protective eye equipment should conform to EN166.

Body protection: Wear suitable protective clothing.

SDS No.: 153483 Page 6 of 11

LOCTITE 262 V001.10

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for

Engineering controls: Ensure good ventilation/extraction.

Good industrial hygiene practices should be observed. Do not eat, drink or smoke while **Hygienic measures:**

working. Wash hands before work breaks and after finishing work.

Section 9. Physical and chemical properties

red Appearance:

liquid Odor: characteristic Odor threshold (CA): No data available. Not applicable **Melting point / freezing point:** No data available.

Specific gravity:

Boiling point: > 150 °C (> 302 °F) Flash point: > 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

No data available. **Evaporation rate:** Flammability (solid, gas): No data available. Lower explosive limit: No data available. **Upper explosive limit:** No data available. < 0.1300000 mbar Vapor pressure: < 300 mbar

(; 20.0 °C (68 °F)no method; 50

°C (122 °F))

No data available. Vapor density: Density: No data available. **Solubility:** No data available. Partition coefficient: n-No data available.

octanol/water:

No data available. Auto ignition: No data available. **Decomposition temperature:** Viscosity: No data available.

VOC content: < 3 %

(2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible

materials:

Peroxides.

Chemical stability: Stable under recommended storage conditions.

Conditions to avoid: Stable

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Acute toxicity estimate (ATE): > 20 mg/l Inhalative toxicity:

Exposure time: 4 h

SDS No.: 153483

V001.10 LOCTITE 262

Test atmosphere: Vapor. Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Page 7 of 11

Acute oral toxicity:

Ethene, homopolymer	Value type	LD50
9002-88-4	Value	> 2,000 mg/kg
	Species	rat
	Method	OECD Guideline 423 (Acute Oral toxicity)
Cumene hydroperoxide	Value type	LD50
80-15-9	Value	550 mg/kg
	Species	rat
	Method	not specified
1,4-Naphthalenedione	Value type	LD50
130-15-4	Value	190 mg/kg
	Species	rat
	Method	not specified

Acute dermal toxicity:

Ethene, homopolymer	Value type	LD50
9002-88-4	Value	> 2,000 mg/kg
	Species	rabbit
	Method	not specified
Cumene hydroperoxide	Value type	LD50
80-15-9	Value	1,200 - 1,520 mg/kg
	Species	
	Method	not specified

Skin corrosion/irritation:

Cumene hydroperoxide	Result	corrosive
80-15-9	Exposure time	
	Species	rabbit
	Method	Draize Test

Serious eye damage/irritation:

Ethene, homopolymer	Result	not irritating
9002-88-4	Exposure time	24 h
	Species	rabbit
	Method	FDA Guideline

Respiratory or skin sensitization:

Ethene, homopolymer	Result	not sensitising
9002-88-4	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Methyl methacrylate	Result	sensitising
80-62-6	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Page 8 of 11 SDS No.: 153483 LOCTITE 262

V001.10

Germ cell mutagenicity:

Ethene, homopolymer	Result	negative
9002-88-4	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	Ames Test
Cumene hydroperoxide	Result	positive
80-15-9	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide	Result	negative
80-15-9	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Methyl methacrylate	Result	negative
80-62-6	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified

Repeated dose toxicity:

Cumene hydroperoxide	Result	
80-15-9	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
Methyl methacrylate	Result	LOAEL=2000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study
Methyl methacrylate	Result	NOAEL=1000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study

Section 12. Ecological information

Ecotoxicity: Do not empty into drains \slash surface water \slash ground water.

Toxicity:

Ethene, homopolymer	Value type	LC50
9002-88-4	Value	> 100 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethene, homopolymer	Value type	EC0
9002-88-4	Value	> 1,000 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	
	Species	
	Method	not specified
Cumene hydroperoxide	Value type	LC50
80-15-9	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide	Value type	EC 50
80-15-9	Value	7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Water flea (Daphnia magna)
	Method	

SDS No.: 153483 V001.10 LOCTITE 262

	Value type	EC50
	Value type Value	
		18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide	Value type	ErC50
80-15-9	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide	Value type	EC10
80-15-9	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	not specified
Methyl methacrylate	Value type	LC50
80-62-6	Value	350 mg/l
	Acute Toxicity Study	Fish
	Exposure time	
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl methacrylate	Value type	EC50
80-62-6	Value	69 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl methacrylate	Value type	EC50
80-62-6	Value	170 mg/l
	Acute Toxicity Study	Algae
	Exposure time	4 d
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	4 d
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methyl methacrylate	Value type	ECO
80-62-6	Value	100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	50 11111
	Method	not specified
1,4-Naphthalenedione	Value type	EC50
130-15-4	Value type Value	0.011 mg/l
130-13-4	Acute Toxicity Study	
	Exposure time	Algae 72 h
	Species	
		Dunaliella bioculata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Ethene, homopolymer	Result	
9002-88-4	Route of application	aerobic
	Degradability	1 %
	Method	ISO 10708 (BODIS-Test)
Cumene hydroperoxide	Result	
80-15-9	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methyl methacrylate	Result	readily biodegradable
80-62-6	Route of application	aerobic
	Degradability	95 %
	Method	EU Method C.4-B (Determination of the "Ready" BiodegradabilityModified
		OECD Screening Test)

SDS No.: 153483 Page 10 of 11

V001.10 LOCTITE 262

1,4-Naphthalenedione 130-15-4	Result	
	Route of application	no data
	Degradability	0 - 60 %
	Method	OECD 301 A - F

Bioaccumulative potential / Mobility in soil:

Cumene hydroperoxide	Bioconcentration factor (BCF)	9.1
80-15-9	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide 80-15-9	LogPow	2.16
	Temperature	
	Method	not specified
Methyl methacrylate 80-62-6	LogPow	1.38
	Temperature	
	Method	not specified
1,4-Naphthalenedione 130-15-4	LogPow	1.71
	Temperature	
	Method	not specified

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

which it is used

Packaging

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Section 15. Regulatory information

Regulatory Information: Decree of Minister of Industry No. 23/M-IND/PER/4/2013 concerning the Revision of Decree of

Minister of Industry No.87/M-IND/PER/9/2009 concerning Globally Harmonized System of

Classification and Labelling of Chemicals

Decree of Minister of Industry No. 87/M-IND/PER/9/2009 concerning Globally Harmonized

System of Classification and Labelling of Chemicals

Global inventory status:

Regulatory list	Notification
TSCA	yes
NDSL	yes
ENCS (JP)	yes
KECI (KR)	yes
PICCS (PH)	yes
IECSC	yes
ISHL (JP)	yes

SDS No.: 153483 Page 11 of 11

V001.10 LOCTITE 262

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.