

FEATURES

- Abrasion, ozone and weather resistant
- Smooth rubber NBR / SBR construction
- In accordance with EN ISO 2398
- Wide temperature range -40°C to +90°C
- Safety factor 3:1

RS PRO Air Hose Black NBR, SBR 29mm x 25m

RS Stock No.: 914-5537



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Brought to you by RS Pro, a range of rubber air hoses, manufactured from a textile reinforced NBR/SBR synthetic rubber. Being Weather and ozone resistant, it is suitable for medium duty applications such as pneumatic air tools and compressors used in the construction and automotive industry and general workshop use. All models are highly reliable and excellent quality.

General Specifications

| | |
|------------------------|----------------------|
| Colour | Black |
| Material | NBR, SBR |
| Number Of Tubes | 1 |
| Application | Compressed Air Tools |

Mechanical Specifications

| | |
|------------------------------|-------|
| Hose Inside Diameter | 19mm |
| Hose Outside Diameter | 29mm |
| Length | 25m |
| Weight Per Metre | 0.7kg |
| Bend Radius | 190mm |

Operation Environment Specifications

| | |
|--------------------------------------|--------|
| Maximum Operating Pressure | 20 bar |
| Minimum Operating Temperature | -40°C |
| Maximum Operating Temperature | +90°C |
| Burst Pressure | 60 bar |

Approvals**Compliance/Certifications**

EN ISO 2398

| RS Stock Number | Internal Diameter | External Diameter | Length | Weight per Meter | Max Working Pressure | Burst Pressure | Bend Radius |
|-----------------|-------------------|-------------------|--------|------------------|----------------------|----------------|-------------|
| 9145540 | 6 mm | 12 mm | 25 m | 0.18 kg | 20 bar | 60 bar | 60 mm |
| 9145543 | 8 mm | 15 mm | 25 m | 0.23 kg | 20 bar | 60 bar | 80 mm |
| 9145525 | 10 mm | 17 mm | 25 m | 0.29 kg | 20 bar | 60 bar | 100 mm |
| 9145534 | 13 mm | 21 mm | 25 m | 0.43 kg | 20 bar | 60 bar | 130 mm |
| 9145537 | 19 mm | 29 mm | 25 m | 0.7 kg | 20 bar | 60 bar | 190 mm |
| 9145531 | 25 mm | 36 mm | 25 m | 1.0 kg | 20 bar | 60 bar | 250 mm |