# Eaton FWP-60B

# Catalog Number: FWP-60B

Eaton Bussmann series FWP high speed fuse, 250 Vac/dc, 60A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud

## General specifications

**Product Name** 

Catalog Number

Eaton Bussmann series high speed

FWP-60B

cylindrical fuse

**UPC** 

051712796002

EAN

Product Length/Depth

5027590500999

102 mm

**Product Height** 

Product Width

21 mm

21 mm

**Product Weight** 

Warranty

93.6 g

Not Applicable

Compliances

Certifications
CSA Certified

CE Marked

**UL** Recognized



# Product specifications

#### Rated voltage DC

700 V

Interrupt rating

200 kAIC Vac

50 kAIC at 700 Vdc

Center-to-center distance of connections

89.7 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC/DC

Mounting method

Stud

**Amperage Rating** 

5 A

Fuse type

FWP-B

Fuse system (according to IEC 60269)

Other

Rated switching capacity

200 A

Voltage rating

700 Vac, 700 Vdc (UL)

Fuse indicator

Non Indicating

Construction size

Other

Clearing (I2T)

950 at 700 V

Rated voltage AC

700 V

Color

None

Connection

Blade end x blade end

#### Resources

#### Catalogs

Bussmann series complete full line catalog no. 1007

#### Mounting dimension

M8

#### Utilization category

aR (accompanied semiconductor protection)

#### Watt losses

15.5 W

#### Type

High speed fuse

#### Fuse shape

Center bolted tags

#### Breaking capacity

200 kA

#### Class

Class aR

#### Pre arc (I2T)

210

#### Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

#### Voltage type

AC/DC

## Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia