

Portable Self-contained Emergency Wash Station



Front



Side

Model		SDEEWT60
Tank	Material	Stainless SUS304# material
	Dimension	Ø350 X 750(H)mm
	Volume	60 Liters (15Gallons) , supply for above 15mins washing work
	Safe Valve	Brass pressure relief valve automatically opens at 120psi to prevent vessel over-pressurization
	Pressure Gauge	Pressure gauge provides easy operation for inspection and controlling the pressure
	Liquid-level Indicator	Liquid-level indicator is at the back of tank , you can observe the liquid-level by the red floating ball
	Wheel Pressurization Device	It is easier to move the unit by combining the handle and the caster with tank Easy to pressurize by air pump or air compressor
Equipment	Dimension	350(W) X 600(D) X 1200(H) mm
	Eyewash height	1140 mm
	Eyewash pipe	1/2" SUS304# stainless
	Spray head bore	3/8" SUS304# (PT)
	Spray head	Nylon material , Ø50mm x 44mm(H) , each head has a "flip top" dust cover, internal flow control and filter
	Activator	Hand push plate
	activated valve	1/2" brass ball valve
Water Hose	Material	Brass body with special process PVDF seal for avoiding leaking
	Handle	Aluminum material , coating yellow PVC
	Hose	1/4" blue PU hose tube
	Activator	Squeeze the lever handle and the locking clip engages automatically, providing "hands free" operation. Valve stays open until locking clip is released
Features		1. All pipes are stainless SUS304 # material , with special antirust process
		2. Indication sign (380x600mm , Chinese & English language with graphic) affixed to tank