



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|-------------------------------|
| Main Input Voltage | 12 V |
| Product or component type | Replacement battery cartridge |
| Main Output Voltage | 12 V |
| Battery type | Lead-acid battery |
| Provided equipment | User manual |

Batteries & Runtime

| | |
|--|------------------|
| Battery location | Internal battery |
| Number of battery blocks per string | 6 |
| Number of battery free slots | 0 |
| Number of battery filled slots | 0 |
| Device mounting | Built-in |
| Battery voltage | 12 V |
| Number of battery replacement quantity | 1 |

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 151 mm |
| Width | 99 mm |
| Depth | 65 mm |
| Net weight | 2.68 kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |

Output

| | |
|------------------|------|
| Battery capacity | 9 Ah |
|------------------|------|

Conformance

| | |
|------------------------|---------------------|
| Product certifications | UL 1778 5th edition |
| Standards | UL 1778 5th edition |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

| | |
|---------------------------------------|------------------|
| Ambient air temperature for operation | 0...40 °C |
| Operating altitude | 0...10000 ft |
| Relative humidity | 0...85 % |
| Ambient air temperature for storage | -15...50 °C |
| Storage altitude | 0.00...3048.00 m |
| Storage Relative Humidity | 0...95 % |

Packing Units

| | |
|------------------------------|----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 19.5 cm |
| Package 1 Width | 39.5 cm |
| Package 1 Length | 49.5 cm |
| Package 1 Weight | 18 kg |
| SCC14 | 50731304427198 |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|