# ABS box IP66 IK07 RAL7035 Int.H175W150D100 Ext.H193W164D105 Transp.cover H40

NSYTBS191610HT

#### Main

*******	
Range	Thalassa
Product name	Thalassa TBS
Device application	Multi-purpose
Category	Industrial box
Height	192 mm
Width	164 mm
Depth	105 mm
Internal height	175 mm
Internal width	150 mm
Internal depth	100 mm
Enclosure mounting	Wall mounted
Device composition	1 body 1 cover 4 cover screw
Body type	One piece moulded
Type of front cover	High transparent cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

#### Complementary

Material	ABS (acrylonitrile butadiene-styrene)
Colour	Grey (RAL 7035) Transparent
Standards	IEC 62208
Product certifications	TÜV
Electrical insulation class	Class II
IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK07 conforming to IEC 62262
Glow wire resistance	650 °C conforming to IEC 60695-2-11

-1540 °C
-2560 °C
0.54 kg

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	540.0 g
Package 1 Height	12.0 cm
Package 1 width	17.0 cm
Package 1 Length	20.5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	17
Package 2 Weight	10.4 kg
Package 2 Height	40.0 cm
Package 2 width	40.0 cm
Package 2 Length	60.0 cm
Unit Type of Package 3	PAM
Number of Units in Package 3	425
Package 3 Weight	275.0 kg
Package 3 Height	215.0 cm
Package 3 width	100.0 cm
Package 3 Length	120.0 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	Product Environmental Profile

### **Contractual warranty**

Warranty	18 months	
----------	-----------	--