



Datasheet

Stock No: 770-692

ENGLISH

RS Pro Beige

Polyetheretherketone (PEEK)

Rod, 300mm x 20mm Diameter



Product Details:

Victrex® PEEK 450G

Typical applications include valve seats in steam and water mixers, components in a high temperature diesel engine turbo actuators etc.

- Continuous working temperature approximately 250°C
- No significant degradation in steam or high pressure water environments
- Can absorb over 1000 Mrads of radiation without appreciable loss of mechanical properties
- Excellent resistance to a wide range of organic and inorganic liquids, and resistant to all common solvents
- Fawn in colour



ENGLISH

Max Service Temperature (Long Term)	260°C
Elongation	5 %
Tensile Strength MPa	92
Hardness (Rockwell-Shore D)	M99 (Rockwell)
Flammability Rating	UL 94 V-0
Water Absorption	0.5 %

Note: No. Per Lot is 1

®Victrex is a registered trade mark of Victrex Ltd

PEEK

PEEK (Polyetheretherketone) high performance thermoplastics are chemical, abrasion and impact resistant. They possess good machine ability and self-lubricating properties.

Specifications:

Colour:	Beige
Length:	300mm
Material:	PEEK
Form:	Rod
Rod Diameter:	20mm
Density:	1.32g/cm ³
Tensile Strength:	95 MPa
Flammability Rating:	UL 94 V-0
Hardness:	M 99 Rockwell
Water Absorption:	0.5%
Maximum Operating Temperature:	+260°C
Elongation:	25%