

ENGLISH

Datasheet

RS Pro Tap Wire Splice Connector, Yellow, Insulated 12 → 10 AWG

RS Stock No: 510-4826



Product Details

RS Pro tap wire splice connector in yellow colour, is insulated and has wire size of 12 to 10 AWG. This quick splice IDC wire splice connector made from brass with colour coded PP insulation. This quick splice provides a simple and time saving wire connection method. The splice is simply placed over the existing wire, the additional wire inserted and the block crimped can then be crimped with pliers. This IDC quick splice is available for inline and T-tap wire connections and accepts various wire and tab sizes.

Features and Benefits

- Quick splice IDC wire splice connectors made from brass with a colour coded nylon insulation
- · Quick splice provide an simple and time saving wire connection method
- Splice is simply placed over the existing wire, the additional wire inserted and the block crimped can then be crimped with pliers



ENGLISH

Specifications:

| Colour | Yellow |
|-------------------------|--------------|
| Contact Material | Brass |
| Insulation | Insulated |
| Insulation Material | PP |
| Shrouded | Shrouded |
| Splice Type | Тар |
| Maximum Wire Size (AWG) | 10 AWG |
| Maximum Wire Size (mm²) | 6 mm² |
| Minimum Wire Size (AWG) | 12 AWG |
| Minimum Wire Size (mm²) | 4 mm² |
| Overall Length | 34.5 mm |
| Wire Size | 12 to 10 AWG |
| Current Rating | 35 to 50 A |
| Temperature Rating | +105°C |
| Voltage Rating | 600 V |
| Width | 20.5 mm |
| | |