



# WALL TEX

**Water-based Acrylic Paint  
for Interior and Exterior use.**

## The Professional Painters' Choice

- *Water Resistance & Repelling.*
- *Excellent 1 coat coverage.*
- *Strong Bonding, it resist washing and brushing.*
- *Ideal for commercial & Residential Properties*
- *Easy to Apply by brush, roller or spray.*

## Matt Finish

*Silky Smooth Texture, washable and can be tinted with color.*

## APPLICATION

- Surface Preparation:** Priming is needed if the surface is powdery.  
Test painting on a small area, do a Pull-out Tape Test, before beginning painting to the whole area.
- Diluent:** Water.
- Re-Coating Time:** 30 minutes to 1 hour.

## Drying and Curing Time

1. Painting should not be carried out before the rain.
2. Theoretical Coverage: 300 g / m<sup>2</sup> @ 50 micron
3. Recommended Dry Film Thickness: 120-150 m 1 to 2 coats
4. Dry to the touch: 30 minutes
5. Hardening Time: 2 hours
6. Full Curing till insoluble in water: 3 hours
7. Recoating Intervals: 30 minute minimum, Maximum unlimited.



# WALL TEX

**Water-based Acrylic Paint  
for Interior and Exterior use.**

## ***Weather Conditions:***

**It is recommended to carry out painting in fair weather.**

**Paint works should not be carried out in damp or rainy days.**

- Air temperature: 10 - 40 °C
- Relative Humidity: 35 – 75 %
- Surface temperature: 5 °C to approximately 40 °C.

## ***Cleaning of Equipment***

1. Immerse the spray gun in clean water during the intervals between spraying, to prevent clogging of the nozzle. Rinsing water should be replaced periodically.
2. When painting is completed, the entire set of equipment should be cleaned thoroughly with water + detergent.
3. Extra care should be taken when cleaning the spray gun to prevent clogging of the nozzle.

## ***Technical Data:***

1. Toxicity: Free from copper, lead, mercury and tin,
2. Colours: White, Cream, Beige Viscous Liquid
3. Shelf Life: 24 months

## ***Storage:***

1. The product is guaranteed when stored under normal temperature and humidity in sealed condition.
2. No special precautions are required against fire.
3. If there is long-term exposure to frost during storage, the Liquid Solution may be separated into 2 phases. The liquid solution should be stirred before use to ensure homogeneity.

***Packing:*            5 kg-pail,            20 kg-pail.**

## ***Disclaimer:***

*The information provided in this brochure is ensured to be as accurate as possible at the time of inclusion, however there may be inadvertent and occasional errors which may have slipped from our notice. Warrior Pte Ltd does not guarantee and make no representations or warranties of any kind about the information, advice and opinions provided and reserves the right to make changes and corrections at any time, without prior notice to any parties. Warrior Pte Ltd accepts no liability for any inaccuracies or omissions in its brochure and any decisions made based on information and opinions contained in the brochure is the sole responsibility of the user*