

ENGLISH

Datasheet

RS Pro Uninsulated Tin Plated Crimp Ring Terminal, M6 Stud Size, 1.5mm² to 2.5mm², 16AWG to 14AWG

RS Stock No: 208-2593



Features and Benefits

- Sheet formed terminal
- Copper contacts
- Uninsulated

Specifications:

| - 1 | |
|-------------------------|-------------|
| Contact Material | Copper |
| Contact Plating | Tin |
| Inner Ring Diameter | 6.4 mm |
| Insulation | Uninsulated |
| Maximum Wire Size (AWG) | 14 AWG |
| Maximum Wire Size (mm²) | 2.5 mm² |
| Minimum Wire Size (AWG) | 16 AWG |

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.



ENGLISH

| Minimum Wire Size (mm²) | 1.5 mm ² |
|-------------------------|---------------------|
| Outer Ring Diameter | 11.6 mm |
| Overall Length | 26.7 mm |
| Stud Size | 1/4 in |
| Thickness | 0.8 mm |
| Wire Size | 16 to 14 AWG |
| Temperature Rating | +75°C |
| Amperage Rating | 18 to 30 A |
| Voltage Rating | 600 V |
| Type | Butted Seam Barrel |