

## FEATURES

- Pre-punched
- Quick and easy install
- Clean black finish
- Up to 85°C operating temperature
- Wipe clean

## RS PRO Black Slotted Panel Trunking - Closed Slot, W60 mm x D60mm, L2m, PVC

RS Stock No.: 301-2135



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

RS PRO closed slot industrial trunking comes in black PVC, giving that clean modern finish to any work area. The pre-punched flat back allows you to organise your cables fixing them to the area the trunking will be applied to. Featuring a clip-on lid, allowing for a simple yet effective installation and secure cable organisation, whilst also allowing for quick and easy cable access. Our trunking is a box shape with a maximum operating temperature of 85°C, ideal for all of your cable and accessories management needs whilst providing that perfect finish

## General Specifications

<b>Trunking/Chain Type</b>	Slotted Panel Trunking
<b>Material</b>	PVC
<b>Colour</b>	Black
<b>Fire Behaviour</b>	Circuit Integrity; Fire Resistant; Flame Retardant
<b>UV Resistance</b>	
<b>Type of Fastening</b>	Bottom perforation; Self-adhesive
<b>Angle</b>	90°
<b>Applications</b>	Offices and indoor work spaces, at various lengths; Electrical workshops, Schools, Hospitals, Hotels and anywhere with customers or staff walking amongst cables

## Mechanical Specifications

<b>Length</b>	2m
<b>Width</b>	60mm
<b>Depth</b>	60mm
<b>Internal Diameter</b>	20mm; 40mm
<b>Slot Type</b>	Closed
<b>Slot Gap</b>	8mm
<b>Minimum Bend Radius</b>	100mm; 75mm
<b>Dielectric Strength</b>	>30kV/mm

## Operation Environment Specifications

<b>Operating Temperature Range</b>	-20°C to 70°C
<b>Maximum Service Temperature</b>	80°C

## Approvals

<b>Standards Met</b>	CE, CSA, RoHS Compliant, UL 94 V-0, UL 94 V-2, UL E97527, CSA 82854, UL 94 V-2
----------------------	--