



Main

Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	White

Complementary

Device mounting	Surface Flush
Wiring device mounting	Flush Surface
Rated current	20 A at 250 V AC 50 Hz
Local signalling	Neon
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 1 x 6 mm ² for stranded cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	32.2 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	IEC 60669-1 SS 227-1 GB 16915.1 BS EN 60669-1 MS IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	125.848 g
Unit Type of Package 2	BB2
Number of Units in Package 2	8
Package 2 Height	9.5 cm

Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.007 kg
Package 3 Height	21 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile