RPZF4

Socket, Harmony, for RPM4 power relays, 16A screw clamp terminals, mixed contact





Main

| Range of product | Harmony Electromechanical Relays |
|-------------------------------------|---|
| Product or component type | Socket |
| Contact terminal arrangement | Mixed |
| | |
| Product compatibility | Plug-in relay RPM with 4 C/O contact |
| Product compatibility Shape of pin | Plug-in relay RPM with 4 C/O contact Flat |
| | <u> </u> |

Complementary

| [lth] conventional free air thermal current | 16 A | |
|---|--|--|
| [Ue] rated operational voltage | < 250 V | |
| Tightening torque | < 1 N.m for M3.5 screw(s) | |
| Fixing mode | By screw (panel) Clip-on (35 mm symmetrical DIN rail) | |
| Marking | CE | |
| Width | 50 mm | |
| Net weight | 0.094 kg | |
| [Uimp] rated impulse withstand voltage | 4 kV | |
| Overvoltage category | III | |
| Pollution degree | 3 | |

Environment

| Connections - terminals | - screw clamp terminals, flexible cable with cable end 1 x 0.51 x 2.5 mm² / AWG 20AWG 14 - screw clamp terminals, solid cable without cable end 1 x 0.51 x 1.5 mm² / AWG 20AWG 16 - screw clamp terminals, flexible cable with cable end 2 x 0.52 x 2.5 mm² / AWG 20AWG 14 |
|---------------------------------------|--|
| | screw clamp terminals, solid cable without cable end 2 x 0.52 x 1.5 mm² / AWG 20AWG 16 |
| Standards | IEC 61984 |
| Product certifications | UL CSA |
| Ambient air temperature for storage | -4085 °C |
| Ambient air temperature for operation | -4055 °C |
| IP degree of protection | IP20 conforming to EN/IEC 60529 |
| Dielectric strength | 2500 V |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 2.994 cm | |
| Package 1 Width | 5.03 cm | |
| Package 1 Length | 8.379 cm | |
| Package 1 Weight | 101.0 g | |

| Unit Type of Package 2 | BB1 |
|------------------------------|----------|
| Number of Units in Package 2 | 10 |
| Package 2 Height | 6.6 cm |
| Package 2 Width | 8.8 cm |
| Package 2 Length | 25.1 cm |
| Package 2 Weight | 1.01 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 110 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 11.65 kg |

Offer Sustainability


| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | ₫Yes |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |


Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|

Dimensions

mm in.






- (1) Relays
- (2) Protection module
- (3) Maintaining clamp

RPZF4

Wiring Diagram



Symbols shown in blue correspond to Nema marking.