


## **FEATURES**

- IP67
- Pre-wired with 500 mm partially stripped cable
- Straight plugs and sockets
- 4, 5, 8 and 12 pole versions

# RS PRO M12 MALE FRONT PANEL MOUNT CONNECTOR 8 PIN 500MM PVC CABLE

RS Stock No.: 2500746



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



#### Product Description ATTRIBUTE 1

#### **RS Pro M12 Panel Mount Connectors**

From RS PRO, a selection of M12 circular connectors designed for panel mounting. The sensor style connectors have an M12 threaded interface and industry standard A coding preventing miss-mating. Conveniently pre-terminated with partially stripped wires the RS PRO range is easy to incorporate into any automation or sensory application. With an IP67 ingress rating, the RS PRO panel mount connectors are ideally suited to harsh environments that demand a more rugged connection solution.

#### Features & Benefits

- IP67
- Nylon 66 contact carrier
- PG9 clamp nut
- Pre-wired with 500 mm partially stripped cable
- Straight plugs and sockets
- 4, 5, 8 and 12 pole versions

### Applications

The RS PRO series of M12 panel mount connectors are generally used in industrial applications. They are typically used when connecting to sensors and actuators. Some of the most popular areas are

- Instrumentation
- Process control
- Robotics
- Assembly lines
- Factory automation
- Industrial automation

#### **General Specifications**

Rated Operational Voltage	30 V
Current Rating	2A
Insulation Resistance	>= 100 MΩ
Temperature Range	-25°C +75°C
Mounting	Front (M12 x 1)
Coding	A-Coded

## **RS PRO M12 PANEL MOUNT CONNECTOR**



Material Specifications	
Housing Material	Brass Ni Plated
Contact	Cu-Zn
Contact Plating	Gold Flash
Contact Carrier	Nylon 66
O-Ring	Neoprene
Pole	8
Clamp Nut	PG9

#### Cable Specifications

Cable Length-L	500 mm
Cross Section of Wire	0.25 sq. mm
Cable Type	PVC
Termination	Partially Stripped

Protection Category		
Degree of Protection	IP67	

Additional Information		
Custom Tariff Number	85369090	

Approvals	
Standards Met	IEC 61076-2-101



Connection Diagrams / Assembly Diagrams / Illustrations / Accessories

