



Overview

Lead time Usually Ships within 4 Weeks



Main

Area	Spacial
Category	Lifting accessory
Product or component type	Lifting eye
Application	Multi-purpose
Mounting location	Enclosure top
Mounting support	Directly in the axis of the uprights
Range compatibility	Spacial Spacial SF Spacial Spacial SFHD Prisma Prisma PH Spacial Spacial SFM
Device composition	4 eyebolt
Quantity per set	Set of 1

Complementary

Material	Cast steel
Surface finish	Galvanized
Fixing mode	Screwed
Permanent permissible load	340 kg for 1 eyebolt vertical direction
Height	62.5 mm
Width	55 mm
Depth	24 mm
Diameter	29 mm
ISO thread	M12

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	10.000 cm
Package 1 Length	10.500 cm
Package 1 Weight	771.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	24

Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	18.924 kg
Unit Type of Package 3	P12
Number of Units in Package 3	192
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	163.392 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------