



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Product or component type	Battery backup
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual

### Batteries & Runtime

Device mounting	Stand alone battery stack
Battery life	4...6 year(s)
Battery voltage	24 V
Battery capacity	18 Ah
Number of battery filled slots	2
Number of battery free slots	0
Number of battery replacement quantity	1
Battery power in VAh	372 VAh

### Physical

Colour	Black
Height	30.1 cm
Width	11.2 cm
Depth	38.2 cm
Net weight	13.4 kg
USB compatible	No

### Conformance

Product certifications	TÜV
------------------------	-----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Ambient air temperature for storage	-15...45 °C
Ambient air temperature for operation	0...40 °C
Operating altitude	0...30000 ft
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40 cm
Package 1 Width	24 cm
Package 1 Length	49.1 cm
Package 1 Weight	14.569 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	24
Package 2 Height	135 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	349.656 kg
SCC14	10731304268786

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------