

FEATURES

- Contact rating of 4 A and 16 A
- NC switch configuration
- Supply voltage of 230VAC
- Temperature range of +5°C to +30°C
- Surface mounting with a thermoplastic front cover
- Fitted with a shunt accelerator heater
- Suitable for industrial and commercial applications

RS PRO Thermostats, +5 → +30 °C

RS Stock No.: 375-0130



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Need to regulate the temperature of your interior spaces? This RS PRO thermostat is fitted with a shunt accelerator so you will benefit from a low switching differential and more accurate regulation of the temperature inside your building. For convenient installation, the unit is designed to be surface mounted.

As an RS PRO branded product, this thermostat has been stringently tested for durability and safety. There are two models available: standard and tamperproof. The standard version includes a front-mounted, graduated temperature adjustment dial. In addition to the standard features, the tamperproof edition includes a plain front cover to conceal the adjustment control. It has a temperature setback of +6°C, which makes it an ideal choice where frost protection is required.

General Specifications

Switch Configuration	NC
Temperature Range	+5°C to +30°C
Maximum Temperature	+30°C
Minimum Temperature	+5°C
Colour	White
Additional Features	Surface mounting with a thermoplastic front cover
Applications	Warehouses, Car Parks, Walkways, Construction areas, Parks and gardens, Home security

Electrical Specifications

Supply Voltage	230VAC
Current Rating	4 A, 16A

Mechanical Specifications

Mounting Method	Surface mounted
------------------------	-----------------

Approvals

Compliance/Certifications	ANSI/ESD S20.20:2014 and BS EN 61340-5-1:2007
----------------------------------	---

