

## Features

- For Use With:  
Universal  
Rectangular Alu
- Mounting: Screw
- Thermal Resistance  
3.7°C/W

## RS PRO Heatsinks

RS Stock No.: 7898592



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

**Push pin type BGA heatsink suitable for surface mount chip cooling and various other applications.**

## General Specifications

For Use With	Universal Rectangular Alu
Material	Aluminium
Mounting	Screw
Application	High Power Semiconductor Device, Optoelectronic Device
Finish	Anodized
Notes	<ul style="list-style-type: none"><li>• Thermal Resistance is calculated based on a distributed heat load and vertically mounted fins anodised heatsink with a 60°C temperature.</li><li>• Under general operating conditions the thermal mounting arrangement of the device is not know and therefore the figures should be used as a guide to selection.</li><li>• We recommend that the effectiveness of any heatsink is tested in the specific operating environment in which it will be subjected.</li></ul>

## Mechanical Specifications

Length	75mm
Width	50mm
Height	28mm
Dimension	75 x 50 x 28mm

## Electrical Specifications

Thermal Resistance	3.7°C/W
--------------------	---------

Drawing below is for illustration purposes only. If any further information is required please contact us.

