




Benefits

- Classic design with build-in driver
- Hybrid Reflector Technology to offer superb beam control quality
- Rotation 330° / Inclination 90°
- Extra long lifespan of 50,000h
- High-quality aluminum finishing

Application



Model	Item Description	W	PF	lm	lm/W	CRI	Beam Angle	Life Span	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
FTA70100v0+025D-BK24	MARCO TR 37W 3000K 25D BK	37	0.9	3300	89	80	25°	50000	120*120*230	380*480*260	12
FTA70100v0+045D-BK24	MARCO TR 37W 3000K 45D BK	37	0.9	3300	89	80	45°	50000	120*120*230	480*380*255	12
FTA70100v0+025D-BK24	MARCO TR 37W 4000K 25D BK	37	0.9	3500	95	80	25°	50000	120*120*230	480*380*255	12
FTA70100v0+045D-BK24	MARCO TR 37W 4000K 45D BK	37	0.9	3500	95	80	45°	50000	120*120*230	480*380*255	12
LA10056/BK24	HONEYCOMB LOUVER FOR MARCO TR 37W	/	/	/	/	/	/	/	/	/	10

Technical Specifications	
CRI	80
Colour Consistency (SDCM)	≤ 6
Dimmable	No
Housing Colour	Black
IP	IP20
IK	IK02
Driver integrated (Yes/No)	Yes

Electrical Supply	
Frequency (Hz)	50/60Hz
Voltage (V)	220V-240V
AC/DC	AC

Mechanical Properties	
Optical Material	PC
Housing Material	AL

Application Conditions	
Operating Temperature	-20°C~40°C
Application Temperature	25°C
Storage Environment	-25°C~50°C

Dimensional Drawing

