

## FEATURES

- Hook up wire is frequently used in control panels, automotive, meters, ovens, internal wiring of computers, electronic equipment, business machines and appliances.
- MPPE insulation
- Easy to handle, strip and terminate
- UL Style 11028
- Flammability Test: VW-1
- Rated Voltage: 600V
- Rated Temperature: 105°C
- Size(AWG): 18

## RS PRO UL11028 Slate, 0.81 mm<sup>2</sup> Hook Up Wire, 305m

RS Stock No.: 208-1086





RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

*Hook up wire is frequently used in control panels, automotive, meters, ovens, internal wiring of computers, electronic equipment, business machines and appliances.*

## General Specifications

<b>Type</b>	Equipment Wire/ hook-up wire
<b>Cores Number</b>	1C
<b>Conductor Material</b>	Tinned Copper
<b>Cross Sectional Area</b>	0.81mm <sup>2</sup>
<b>Conductor Size of Strands</b>	0.25 ± 0.008mm
<b>Conductor Number of Strands</b>	16
<b>Conductor Strand diameter (mm)</b>	1.17mm
<b>American Wire Gauge</b>	18
<b>Insulation Material</b>	MPPE
<b>Insulation Colour</b>	Slate
<b>Insulation Wall Thickness</b>	0.27mm
<b>Insulation Min Thickness</b>	0.18mm
<b>Insulation Diameter</b>	1.70 ± 0.10mm
<b>Wire Style</b>	UL11028
<b>Fire Behaviour</b>	Flammability Test: VW-1
<b>Cable Marking</b>	E254881  AWM STYLE 11028 18AWG 105°C 600V VW-1 c  AWM I A 105°C 600V FT1 -LF- - HF- ELETECK

**Electrical Specifications**

<b><i>Voltage Rating</i></b>	<b>600V</b>
<b><i>Conductor Resistance</i></b>	23.2Max Ohms/1000m @ 20degC
<b><i>Spark Test</i></b>	15 x overall diameter

**Operation Environment Specifications**

<b><i>Minimum Operating Temperature</i></b>	<b>-40°C</b>
<b><i>Maximum Operating Temperature</i></b>	105°C
<b><i>Operating Temperature Range</i></b>	-40°C to 105°C

**Approvals**

<b><i>Compliance/Certifications</i></b>	<b>UL 11028</b>
<b><i>Standards Met</i></b>	RoHS Compliant
<b><i>Declarations</i></b>	REACH