

Features

- Extended sensing distance;
- ASIC design; safe and reliable;
- Perfect choice for metallic target detection

RS PRO Inductive Sensor

RS Stock No.: 2522032



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Specifications

Mounting	Flush
Rated distance Sn	1.5mm
Assured distance Sa	0...1.2mm
Shape size	M5*0.5
Output	PNP NO
Supply voltage	10...30 VDC
Standard target	Fe 5*5*1t
Switch point offset [%/Sr]	≤±10%
Hysteresis range [%/Sr]:	1...20%
Repeat accuracy	≤3%
Load current	≤100mA
Residual voltage	≤2.5V
Current consumption	≤10mA
Protection circuit:	Reverse polarity
Output indicator:	Red LED
Ambient temperature	-25°C...70°C
Ambient humidity	35-95%RH
Switch frequency	1200Hz
Voltage withstand	...
Insulation resistance	≥50MΩ(500VDC)
Vibration resistance	10...50Hz(1.5mm)
Housing material	Stainless steel
Connection	2m PUR cable

Protection Category

IP Rating	IP67
-----------	------

Additional Information

Custom Tariff Number/HS code	903180
------------------------------	--------

Approvals

Compliance/Certifications	CE
---------------------------	----

Dimensions and Wiring

