

### **FEATURES**

- Exposed welded junction for fast response
- Durable Teflon PFA insulation for resistance to oils
- Acid, fluids and good mechanical strength and flexibility
- Also suitable for other fine wire work

# RS PRO Type K Thermocouple 5m Length, 1/0.3mm Diameter $\rightarrow$ +250°C

RS Stock No.: 847-9707



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



**Product Description** 

From RS Pro a range of Type K and Type T fine wire temperature sensing thermocouples that meet ANSI MC96.1 standards with class 1 tolerance for optimum accuracy. These Type K and type T wire temperature sensors consist of a durable Teflon PFA insulated twin-twisted lead and a single element exposed welded junction for a fast response time.

#### **General Specifications**

Thermocouple Type	Туре К
Temperature Measurement Range	-75 to 250°C
Construction	Durable construction with choice of conductor size, 1/0.2, 1/0.3mm solid or 7/0.2mm stranded
Measuring Junction	welded exposed junction
Application	Ideal for test & development, temperature mapping and OEM applications

#### **Mechanical Specifications**

Probe Diameter	1/0.3mm
Probe Length	5m
Termination Type	Cable
Weight	4Kg

Approvals

Standards Met	ANSI
Compliance/Certifications	ANSI MC96.1, BS EN 60584-3:2008

## Thermocouples





Т/С Туре	Conductors	Length	Termination	+Positi tail wir		-Negativ tail wire		Allied Code		RS order Code
'K'	1/0.2mm	1 metre	Mini plug	Green		White		70643600	)	363-0250
'K'	1/0.2mm	2 metre	Mini plug	Green		White				110-4482
'K'	1/0.2mm	5 metre	Mini plug	Green		White				123-6306
<b>'K'</b>	1/0.2mm	10 metre	Mini plug	Green		White				123-6307
<b>'</b> 1'	1/0.2mm	1 metre	Mini plug	Black		White		70643599	)	363-0244
37	1/0.2mm	2 metre	Mini plug	Black		White				123-6308
'J'	1/0.2mm	5 metre	Mini plug	Black		White				123-6309
<b>л</b> ,	1/0.2mm	10 metre	Mini plug	Black		White				123-6310
'T'	1/0.2mm	1 metre	Mini plug	Brown		White		70643601	L	363-0266
'T'	1/0.2mm	2 metre	Mini plug	Brown		White				123-6311
'T'	1/0.2mm	5 metre	Mini plug	Brown		White				123-6312
'Τ'	1/0.2mm	10 metre	Mini plug	Brown		White				123-6313
т/с	Туре	Conductors	Cores		Reel Le	ength	Allied	l code	RS o	order code
J		1/0.2mm	+Black/-White		25 met	tres	7065	7194	827	-5980
J		1/0.2mm	+Black/-White		50 met	tres	7065	7195	827	-5984
J		1/0.315mm	+Black/-White		25 met	tres	7065	7198	827	-5993
J		1/0.315mm	+Black/-White		50 met	tres	7065	7199	827	-5996
К		1/0.315mm	+Green/-White		25 met	tres	7065	7200	827	-6000
К		1/0.315mm	+Green/-White		50 met	tres	7065	7205	827	-6019
Т		1/0.315mm	+Brown/-White	9	25 met	tres	7065	7208	827	-6028
т		1/0.315mm	+Brown/-White	9	50 met	tres	7065	7206	827	-6022
J		1/0.508mm	+Black/-White		25 met	tres	7065	7197	827	-5990
J		1/0.508mm	+Black/-White		50 met	tres	7065	7201	827	-6003
K		1/0.508mm	+Green/-White		25 met	tres	7065	7203	827	-6012
К		1/0.508mm	+Green/-White	2	50 met	tres	7065	7204	827	-6016
J		7/0.2mm	+Black/-White		25 met	tres	7065	7202	827	-6006
К		7/0.2mm	+Green/-White		25 met	tres	7065	7207	827	-6025
т		7/0.2mm	+Brown/-White	e	25 met	tres	7065	7209	827	-6031
		7/0 2	Dial / Miletea		25		7000	7340	007	C004

7/0.2mm

+Pink/-White

25 metres

Ν

827-6034

70657210

## Thermocouples



		Conductors	Cores	Jacket	Reel Length	Allied Code	RS order code	•	
E	Extensi	on:							
k	КΧ	7/0.2mm	+Green/-White	Green	10 metres	70657084	827-5615		
k	КΧ	7/0.2mm	+Green/-White	Green	25 metres	70641729	236-3820		
k	KX	7/0.2mm	+Green/-White	Green	50 metres	70657085	827-5619		
k	KX	7/0.2mm	+Green/-White	Green	100 metres	70646156	611-7889		
k	KX	7/0.2mm	+Green/-White	Green	200 metres	70657088	827-5628		
		7/0 2	BL-L/WEB-	Plant.	10	70044040	240 4752		
-	X	7/0.2mm	+Black/-White	Black	10 metres	70641640	219-4753		
	X	7/0.2mm	+Black/-White	Black	25 metres	70657078	827-5592		
-	IX	7/0.2mm	+Black/-White	Black	50 metres	70657079	827-5596		
	IX	7/0.2mm	+Black/-White	Black	100 metres	70641737	236-3915		
J	JX	7/0.2mm	+Black/-White	Black	200 metres	70657081	827-5606		
1	тх	7/0.2mm	+Brown/-White	Brown	10 metres	70641637	219-4703		
1	тх	7/0.2mm	+Brown/-White	Brown	25 metres	70641734	236-3870		
1	тх	7/0.2mm	+Brown/-White	Brown	50 metres	70657095	827-5653		
1	ТХ	7/0.2mm	+Brown/-White	Brown	100 metres	70651749	762-1146		
	ТХ	7/0.2mm	+Brown/-White	Brown	200 metres	70657098	827-5662		
١	NX	7/0.2mm	+Pink/-White	Pink	10 metres	70641635	219-4668		
1	NX	7/0.2mm	+Pink/-White	Pink	25 metres	70657091	827-5637		
1	NX	7/0.2mm	+Pink/-White	Pink	50 metres	70657089	827-5631		
١	NX	7/0.2mm	+Pink/-White	Pink	100 metres	70657092	827-5640		
		Conductors	Cores	Jacket	Reel Leng	th Allied	RS or	der code	
		conductors	00.05			Code			
Compensa	ating:								
VX (KCB)		7/0.2mm	+Green/-White	Green	10 metres				
VX (KCB)		7/0.2mm	+Green/-White	Green	25 metres				
VX (KCB)		7/0.2mm	+Green/-White	Green	50 metres				
VX (KCB)		7/0.2mm 7/0.2mm	+Green/-White +Green/-White	Green Green	100 metre 200 metre				
VX (KCB)		7/0.2000	+Green/-white	Green	200 metre	-5 7005	000 02/-3	012	
VX (KCB)		13/0.2mm	+Green/-White	Green	10 metres	7065	7086 <b>827-5</b>	621	
VX (KCB)		13/0.2mm	+Green/-White	Green	25 metres	7065	7087 <b>827-5</b>	625	
VX (KCB)		13/0.2mm	+Green/-White	Green	50 metres	7065	7090 <b>827-5</b>	634	
VX (KCB)		13/0.2mm	+Green/-White	Green	100 metre	es 7065	750 <b>762-1</b>	152	
U (RCA)		7/0.2mm	+Orange/-White	Orange	10 metres	7065	7096 <b>827-5</b>	656	
U (RCA)		7/0.2mm	+Orange/-White	Orange	25 metres	7064	611-7 611-7	902	
U (RCA)		7/0.2mm	+Orange/-White	Orange	50 metres	7065	7097 <b>827-5</b>	659	
U (RCA)		13/0.2mm	+Orange/-White	Orange	10 metres	7064	641 <b>219-4</b>	769	
U (RCA)		13/0.2mm	+Orange/-White	Orange	25 metres				
U (RCA)		13/0.2mm	+Orange/-White	Orange	50 metres				
			0-/	Be					

## Thermocouples



<b>Т/С Туре</b>	Conductors	Cores	<b>Reel Length</b>	Allied code	RS order code
КХ	1/0.2mm	+Yellow/-Red	25 metres	70656106	814-0030
КХ	1/0.2mm	+Yellow/-Red	50 metres	70656111	814-0049
КХ	1/0.2mm	+Yellow/-Red	100 metres	70656109	814-0042
KX	7/0.2mm	+Yellow/-Red	25 metres	70656110	814-0046
KX	7/0.2mm	+Yellow/-Red	50 metres	70656113	814-0055
KX	7/0.2mm	+Yellow/-Red	100 metres	70656114	814-0058
KX	1/0.3mm	+Yellow/-Red	25 metres	70656104	814-0024
KX	1/0.3mm	+Yellow/-Red	50 metres	70656107	814-0033
KX	1/0.3mm	+Yellow/-Red	100 metres	70656108	814-0036
TX	1/0.3mm	+Blue/-Red	25 metres	70656121	814-0080
TX	1/0.3mm	+Blue/-Red	50 metres	70656126	814-0099
TX	1/0.3mm	+Blue/-Red	100 metres	70656124	814-0092
TX	1/0.2mm	+Blue/-Red	25 metres	70656125	814-0096
TX	1/0.2mm	+Blue/-Red	50 metres	70656128	814-0106
TX	1/0.2mm	+Blue/-Red	100 metres	70656129	814-0109

Т/С Туре	Conductors	Cores	Jacket	Reel Length	Allied code	RS order code		
Extension:								
KX	7/0.2mm	+Yellow/-Red	Yellow	25 m	70656102	814-0018		
КХ	7/0.2mm	+Yellow/-Red	Yellow	100 m	70656105	814-0027		
кх	7/0.2mm	+Yellow/-Red	Yellow	200 m	70656103	814-0020		
XL	7/0.2mm	+ White/-Red	Black	25 m	70656096	813-9995		
XL	7/0.2mm	+ White/-Red	Black	100 m	70656098	814-0005		
XL	7/0.2mm	+ White/-Red	Black	200 m	70656099	814-0008		
тх	7/0.2mm	+Blue/-Red	Blue	25 m	70656119	814-0074		
тх	7/0.2mm	+Blue/-Red	Blue	100 m	70656122	814-0083		
ТХ	7/0.2mm	+Blue/-Red	Blue	200 m	70656123	814-0086		
Compensating:								
VX (KCB)	7/0.2mm	+Yellow/-Red	Yellow	25 m	70656127	814-0103		
VX (KCB)	7/0.2mm	+Yellow/-Red	Yellow	100 m	70656130	814-0112		
VX (KCB)	7/0.2mm	+Yellow/-Red	Yellow	200 m	70656131	814-0115		