

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS		DOC. NO.	SPC-F005		* Effective: 12/21/98		* DCP No. 680	
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRD	DATE
796	A	RELEASED	HYO	10/9/01	JWM	3/27/02	DJC	3/27/02



Static dissipative dispensers come with a Purity pump that protects against cross contamination by keeping fluid from returning to dispenser. Features an average surface resistivity of $10^9 \sim 10^{10}$ ohm, and can dissipate a $\pm 5000V$ charge in less than 2 seconds at 40% relative humidity.

<p>DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR COMPANY'S CONTROL, WE MAKE NO WARRANTY, WHETHER IN CONNECTION OR OTHERWISE, INTENDED USE AND ASSUME ALL RISK AND LIABILITY.</p>					
<p>UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.</p>		<p>DRAWING TITLE: 6 OUNCE ESD SOLVENT DISPENSER, PURITY PUMP</p>			
DRAWN BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
HISHAM ODISH	10/9/01	A	1466	10N689.DWG	A
CHECKED BY:	DATE:	SCALE:	NTS	U.O.M.: INCHES [mm]	SHEET:
JEFF MCVICKER	3/27/02				1 OF 1
APPROVED BY:	DATE:				
DANIEL CAREY	3/27/02				