


RS PRO Polyurethane Tubing

FEATURES

- Excellent flexibility at low pressure
- Lightweight with good tolerance to wear and chemicals
- Convenient for piping, as it has better flexibility than nylon tube

RS Stock No.:

2351220,2351222,2351223,2351224,2351225,2351226,2351227,2351228,2351229,2351230,2351231



Features

- Excellent flexibility at low pressure
- Lightweight with good tolerance to wear and chemicals
- Convenient for piping, as it has better flexibility than nylon tube

General Specifications

Temperature range	0°C to +60°C
Pressure rating	Vacuum 0.95 bar Values given are based on the short term burst pressure of hose at 20°C using a 3:1 safety factor. Any increase in temperature above 20°C will result in decline in the working pressure values.

Construction

Polyester based PU Shore A 98

Product Description

Part No.	OD	ID	Working pressure	Length	Colour
2351220	4 mm	2.5 mm	10 bar	50 m	Blue
2351222	4 mm	2.5 mm	10 bar	100 m	Transparent blue
2351223	6 mm	4.0 mm	10 bar	50 m	Black
2351224	6 mm	4.0 mm	10 bar	20 m	Clear
2351225	6 mm	4.0 mm	10 bar	20 m	Transparent blue
2351226	8 mm	5.5 mm	10 bar	20 m	Transparent blue
2351227	10 mm	6.5 mm	10 bar	50 m	Blue
2351228	10 mm	6.5 mm	10 bar	20 m	Transparent blue
2351229	12 mm	8.0 mm	10 bar	50 m	Transparent blue
2351230	14 mm	10.0 mm	10 bar	50 m	Blue
2351231	16 mm	11.0 mm	10 bar	50 m	Blue