



## Datasheet Stock No: RS Pro Steel Zinc Plated O Clips



The RS Pro range of double ear O clips also known as lemon clips, 2 ear clips or double ear clips come in a range of sizes starting with a 5mm minimum diameter to 27mm maximum diameter, starting from a 6mm band width to 10mm.

## **Typical Applications:**

Often used for maintenance and OEM applications.

Suitable for applications involving air, fluid, gas and steam hoses of rubber or plastic, and co-axial and other electrical cable.

Also suitable for low pressure hydraulic applications.

## Installation Tips:

Requires closing pincers to install and remove. Both standard closing and side closing pincers can be used or alternatively cable cutters as a matter of course.

To install close one ear fully, the first ear is then closed so the first ear can open slightly. This will build resilience strength allowing the clamp to hold against shrinkage, pressure and vibration caused by wear and tear and temperature changes.

Use side closing pincers if access to ear is limited.

Our range of O clips are also available in Stainless Steel or in a 200 piece Steel O Clip kit by ordering part no: 292524.

Kit Contents								
Clip Size	5-7	7-9	8-11	9-11	11-13			
Quantity	25	25	25	25	25			
Clip Size	13-15	15-18	17-20	20-23	23-27			
Quantity	15	20	15	15	10			





## Please view our full range listing below for all Zinc Plated Steel O Clips

Clip Type	Material	Finish	Band Width	Inside Diameter Minimum	Inside Diameter Maximum	RS Part No.
O Clip	Steel	Zinc Plated	6mm	5 mm	7 mm	436370
O Clip	Steel	Zinc Plated	6mm	7 mm	9 mm	436386
O Clip	Steel	Zinc Plated	7mm	9 mm	11 mm	436392
O Clip	Steel	Zinc Plated	7mm	11 mm	13 mm	436409
O Clip	Steel	Zinc Plated	7.5mm	13 mm	15 mm	436415
				1		
O Clip	Steel	Zinc Plated	8mm	15 mm	18 mm	436421
						-
O Clip	Steel	Zinc Plated	8.5mm	17 mm	20 mm	436437
				1		
O Clip	Steel	Zinc Plated	9mm	20 mm	23 mm	436443
O Clip	Steel	Zinc Plated	10mm	23 mm	27 mm	436459