



Datasheet

RS PRO PG Type Cable Glands, Nickel Plated Brass, IP68, No Locknut

Stock No. 2084379, 2084383, 2084382, 2084380, 2084378, 2084384

EN



Applications

Nickel-plated brass cable glands are robust and extremely suitable for industrial use. They are widely used for New Energy Vehicles, Rail Transit, Wind and Solar, Electric complete set, Automation, TBS, LED and etc.

Specification

Material: Nickel-plated brass
 Fixture material: PA (NYLON), UL94V-2
 Seal: NBR
 O-Ring: EPDM
 Working temperature: -40 to 100 degree centigrade

Attributes

RS Article No.	Thread Size	Material	Max. Cable Dia. mm	Min. Cable Dia. mm	GL mm	Spanner Size mm	IP Rating	Minimum Operating Temp.	Maximum Operating Temp.	Series	Locknut Included
2084378	PG9	Nickel Plated Brass	8	4	6	17	IP68	-40°C	+100°C	A1	No
2084379	PG11	Nickel Plated Brass	10	5	6	20	IP68	-40°C	+100°C	A1	No
2084380	PG13.5	Nickel Plated Brass	12	6	6.5	22	IP68	-40°C	+100°C	A1	No
2084382	PG16	Nickel Plated Brass	14	10	6.5	24	IP68	-40°C	+100°C	A1	No
2084383	PG21	Nickel Plated Brass	18	13	7	30	IP68	-40°C	+100°C	A1	No
2084384	PG29	Nickel Plated Brass	25	18	8	40	IP68	-40°C	+100°C	A1	No