## Product data sheet Characteristics

# WHT35\_GY

# 35A 440V Wheatherproof Surface Mount Triple Pole Isolating Switch IP66





#### Main

Range	Kavacha
Product or component type	Isolating switch
Device short name	W
Device application	Control

#### Complementary

[le] rated operational current	35 A at 440 V AC-22A
Poles description	3P
Motor Rating	M180
Width	82 mm
Height	170 mm
Depth	90 mm

#### **Environment**

IP degree of protection	IP66
Standards	IEC 60947-3
Environmental characteristic	Weatherproof

#### **Packing Units**

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.5 cm
Package 1 Width	9 cm
Package 1 Length	8.3 cm
Package 1 Weight	733.333 g
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	36.5 cm
Package 2 Width	28.5 cm
Package 2 Length	43.5 cm
Package 2 Weight	22000 g
Unit Type of Package 3	P12
Number of Units in Package 3	540
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	414000 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations