



## PRODUCT NUMBER: LA132G Nitri Guard Plus - LA132G

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Preparation of greasy products, production of paints, varnishes.



### Overview

**Reference Number**

LA132G

**Product Type**

Gloves

**Range**

Chemical Protection

**Line**

Heavy chemical

**Brand**

Honeywell

**Brand formerly known as**

NORTH

**Industry**

- Agriculture
- Automotive and Part Manufacturer
- Chemical Industries
- Food Industries
- Industrial Cleaning
- Laboratory
- Petro-chemical
- Water treatment

**Product Use**

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Preparation of greasy products, production of paints, varnishes.

### Features & Benefits

**Feature**

Unsupported nitrile glove. Flocked cotton. Raised pattern. Thickness : 0.38 mm. Length : 33 cm.

**Benefit**

**COMFORT** Its nitrile formula has been selected to give the glove greater elasticity and unrivalled dexterity. The cotton flocked interior provides the user with greater comfort. The glove's rough finish improves the grip, to grasp objects in a greasy or damp atmosphere. Gloves will not swell, sag or weaken from fat absorption. Curved shaped hand provides a natural fit. **RESISTANCE** Nitrile ensures good chemical properties and excellent mechanical characteristics (abrasion). It is particularly suitable for the handling of oils, greases and hydrocarbons. Out performs natural rubber, neoprene and vinyl gloves when exposed to solvents, caustics and animal fats. Avoid contact with solvents containing ketones. **SAFETY**

Category III glove for constant quality. The cuff helps to protect a part of the forearm. HYGIENE Gloves are free of latex proteins which can cause allergic reactions

## Technical Description

### Description

Unsupported nitrile glove. Flocked cotton. Raised pattern. Thickness : 0.38 mm. Length : 33 cm.

### Product Technology

Dipped

### Glove/liner color

Green

### Coating Type

Nitrile

### Length

33 cm

### Thickness

0,38 mm

### Harmlessness

In conformity with the European standards.

### Dexterity

Class 5

### Sizes

7S, 8M, 9L, 10XL, 11XXL

## EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	1
Tear resistance	0
Puncture resistance	1
Cutting resistance (TDM test)	X

## EN 374-3 Resistance to

Resistance to permeation by chemicals	JKL
---------------------------------------	-----

## Certifications

### EU Category PPE

3

### EU Certification

0075/797/162/03/19/1022

### Certifications

- EN (0075/797/162/08/13/0760 EXT04/04/15)

## Additional Information

### User Manual

UI 104

## Maintenance

### Storage Information

Minimum packaging : 12 pairs. Cartons of 144 pairs.

### Care Instructions

In order to keep its properties, this article should not be cleaned.

© Honeywell International Inc.

The logo for ANSAC, featuring the word "ANSAC" in a bold, blue, sans-serif font with a red underline.

### ANSAC TECHNOLOGY (S) PTE LTD

35, Marsiling Industrial Estate Road 3,

#02-01 Singapore 739257

T: (65) 6368 0225 F: (65) 6368 8023

E: [sales@ansac-tech.com.sg](mailto:sales@ansac-tech.com.sg) | [www.ansac-tech.com.sg](http://www.ansac-tech.com.sg)