



ENGLISH

Datasheet

Stock No. 146-6759

RS PRO Capacitive Sensor



Specifications:

Mounting: Nonflush

Rated distance S_n : 10mm (Adjustable)

Assured distance S_a : 0...8mm

Shape size: 20*50*10mm

Output way: PNP

Output status: NC

Supply voltage: 10...30 VDC

Standard target: Fe 34*34*1t

Switch point offset[%/Sr]: $\leq \pm 20\%$

Hysteresis range [%/Sr]: 3...20%

Repeated error: $\leq 3\%$

Load current: $\leq 200\text{mA}$

Residual voltage: $\leq 2.5\text{V}$

Current consumption: $\leq 15\text{mA}$

Protection circuit: Reverse polarity protection

Output indicator: Yellow LED

Ambient temperature: $-10^\circ\text{C} \dots 55^\circ\text{C}$

Ambient humidity: 35-95%RH

Switch frequency: 30 Hz

High pressure resistance: 1000V/AC 50/60Hz 60s

20/09/2017

Insulation resistance: $\geq 50\text{M}\Omega(500\text{VDC})$

Vibration resistance: Complex amplitude 1.5mm 10...50Hz(2H per X,Y,Z direction)

Protection degree: IP67

Housing material: PBT

Connection: 2m PVC cable

Features:

Contactless detection, no damage to the detected target;

High detection precision and fast response frequency;

Able to detect metal and nonmetal objects,with wider application;

Different media in the container can be detected by a non-metallic tube wall.