



### Main

|                           |              |
|---------------------------|--------------|
| Range                     | PratiKa      |
| Product or component type | Wander plug  |
| Device short name         | PratiKa plug |
| Plug, socket category     | Low voltage  |
| Poles description         | 3P + N + E   |
| Network type              | AC           |
| Outlet standard           | Industrial   |

### Complementary

|                                     |   |
|-------------------------------------|---|
| Plug, socket, control station shape | Straight  |
| [In] rated current                  | 63 A  |
| [Ue] rated operational voltage      | 380...415 V                                     |
| Network frequency                   | 50/60 Hz  |
| Ground lug clockwise position       | 6 h   |
| Plug, socket material               | Housing: self-extinguishing engineering polymer |
| Contacts material                   | Pins: nickel plated brass                       |
| Connections - terminals             | Captive screws                                  |
| Cable cross section                 | 6...25 mm <sup>2</sup>                          |
| Cable outer diameter                | 17...31 mm                                      |
| Cable entry                         | Cable gland                                     |
| Thread type                         | Pg 36   |
| Net weight                          | 0.792 kg  |
| Height                              | 265 mm  |
| Width                               | 110 mm  |
| Depth                               | 110 mm  |
| Colour                              | Grey (RAL 7035)                                 |
| Voltage colour                      | Red   |

### Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | IEC 60309-1<br>IEC 60309-2                      |
| IP degree of protection               | IP67 conforming to IEC 60529                    |
| IK degree of protection               | IK08 conforming to EN 62262                     |
| Fire resistance                       | 850 °C conforming to IEC 60695-2-11             |
| Relative humidity                     | 50 % at 40 °C<br>70 % at 30 °C<br>90 % at 20 °C |
| Operating altitude                    | 2000 m  |
| Ambient air temperature for operation | 35 °C ( 86400 s )<br>-25...40 °C                |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 11.3 cm   |
| Package 1 Width              | 11.3 cm   |
| Package 1 Length             | 26.4 cm   |
| Package 1 Weight             | 802.0 g   |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 10        |
| Package 2 Height             | 30.0 cm   |
| Package 2 Width              | 30.0 cm   |
| Package 2 Length             | 40.0 cm   |
| Package 2 Weight             | 8.507 kg  |
| Unit Type of Package 3       | P12       |
| Number of Units in Package 3 | 80        |
| Package 3 Height             | 50.0 cm   |
| Package 3 Width              | 80.0 cm   |
| Package 3 Length             | 120.0 cm  |
| Package 3 Weight             | 80.056 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|