

Datasheet

RS PRO RED 2 CORE MICROPHONE CABLE, 100M

Stock No: 2075318




Technical Specifications:

Conductor	Tinned Copper	Insulation 2 Material	Semi- Conductive PE
Cores Number	2C	Insulation 2 Color	Black
Size(mm²)	0.36	Ave Thickness(mm)	0.30
Construction(±0.008mm)	32/0.12	Min Thickness(mm)	0.24
Stranded Dia.(mm)	0.78	Insulation 2 Dia.(±0.15mm)	3.40
Insulation 1 Material	PE	Nylon Rip Cord	150D
Insulation 1 Color	Natrual, Yellow	Jacket Material	PVC
Ave Thickness(mm)	0.31	Jacket Color	Red (RAL3018)
Min Thickness(mm)	0.25	Ave Thickness(mm)	1.60
Insulation 1 Dia.(±0.10mm)	1.40	Min Thickness(mm)	1.28
Drain Wire(±0.008mm)	30/0.12 Tinned Copper	Outer Dia(±0.20mm)	6.60
Cabling	Yes		

Features & Benefits:

- Operating temperature: -20~+80 °C
- Conductor resistance(20°C Ω/km): 55.5max.
- Insulation DC Resistance(20°C MΩ*Km): 200min.
- Operating voltage: 60 V

Cross Section drawings



Cable Marking: RS PRO 2 Core×0.36mm²
Microphone Cable 60V

Applications:

This multicore microphone cable can be soldered to standard jack and XLR connectors to make custom audio cables that can connect microphones and instruments to mixers or amplifiers. This high-quality audio cable is suitable for:

- Live stages and theatres
- Professional studio setups
- Hobbyist and custom audio setups