Product data sheet Characteristics

NU501318

Double USB Quick Charge A+C, New Unica, 45W, white





Main	
Range	New Unica
Product or component type	USB charger
Device presentation	Mechanism with fixing frame
Condition of use	Indoor

Complementary

Device application	Charger
Device mounting	Flush
Number of modules	2 modules
Type of USB power supply	USB type A + C
Colour tint	White (RAL 9003)
Surface finish	Glossy
[Ue] rated operational voltage	100240 V AC 50/60 Hz
Power consumption in W	0.3 W
Nominal output power	45 W
Service life in hours	30000 h 52.5 W
Socket number	2
Integrated connection type	1 USB type A 5 V DC, maximum load current: 1.5 A 1 USB type C 5 V DC, maximum load current: 3 A
Material	Plastic: housing
Protection type	Short-circuit Surge Overheating Overvoltage Overcurrent
Number of terminals	2 screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	2 x 0.752 x 2.5 mm² for rigid cable(s) 2 x 0.752 x 2.5 mm² for flexible cable(s)
Wire stripping length	7 mm
Provided equipment	Fixing frame
Fixing mode	Screws or claws
Ambient air temperature for operation	040 °C
Height	71 mm
Width	71 mm
Depth	39 mm
Embedding depth	30 mm
Net weight	0.131 kg

Quantity per set	1
Resistance to chemical agents	Resistant to alcohol (70 %)
	Resistant to alcohol (96 %)
	Resistant to A-Lactic Acid
	Resistant to diluted quaternary ammonium
	Resistant to diluted bleach
	Resistant to diluted ammonia
	Resistant to soapy water
	Resistant to crystal cleaner
	Resistant to hydrogen peroxide 10 volumes
	Resistant to hexane

Environment

Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	