



Benefits

- Perfect LED replacement for halogen lamps in applications where the faithful colour reproduction associated with natural light is crucial
- Compact & powerful

Application



Model	Item Description	W	PF	lm	lm/W	CRI	BA	Beam Angle	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
LG2603v1-E14	BULB P45 3W E14 MK 2700K	3.0	0.5	250	83	80	240°	15000	44*44*87	290*242*191	60
LG2603v1-E14	BULB P45 3W E14 MK 4000K	3.0	0.5	250	83	80	240°	15000	44*44*87	290*242*191	60
G45S1-4.9W-F-E27	CLSV1 G45 4.9W E27 FS 3000K	4.9	0.5	500	102	80	240°	20000	44*44*84	290*242*191	60
G45S1-4.9W-F-E27	CLSV1 G45 4.9W E27 FS 4000K	4.9	0.5	500	102	80	240°	20000	44*44*84	290*242*191	60
LG2603v1-E27	BULB P45 3W E27 MK 4000K	3.0	0.5	250	83	80	240°	15000	44*44*84	290*242*191	60
LG2603.5v2-E27	BULB P45 3.5W E27 MK 6500K	3.5	0.5	250	71	80	240°	15000	44*44*84	290*242*191	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Dimensional Drawing

