

FEATURES

- Dimensions of 30.3 mm (L) x 92 mm (W) x 30 mm (D)
- Maximum Voltage (AC) of 400 V
- Maximum Voltage (DC) of 250 V
- Cable connection
- Screw terminal
- DPST pole and throw configuration
- 7 N operating force
- Vertical orientation
- Minimum of 15,000,000 operations
- Snap minimum operating contact
- Thermoplastic fibreglass housing
- Roller lever actuator type

RS PRO, Snap Limit Switch - Thermoplastic Fibreglass, NO/NC, Roller Lever, 400V, IP65

RS Stock No.: 902-6871



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

This easy-to-install snap limit switch is typically used to automatically control mechanical equipment in industrial applications. Featuring a simple, visible operation, it can be used to start, stop or slow down devices when a particular limit is reached. This could be when a part moves past a specific point, or when a pre-programmed number of objects is counted.

General Specifications

Actuator Type	Roller Lever
Pole and Throw Configuration	DPST
Normal State Configuration	NO/NC
Contact Type	Snap
Applications	Warehouses, Car Parks, Walkways, Construction areas, Parks and gardens, Home security

Materials

Housing Material	Thermoplastic Fibreglass
-------------------------	--------------------------

Electrical Specifications

Maximum Current	10A
Maximum AC Voltage	400V
Maximum DC Voltage	250V
Frequency	50Hz
Connection Type	Cable
Terminal Type	Screw
Contact Resistance	<25mOhm max.
Rated Insulation Voltage	500V
Impulse Withstand Voltage	6KV

Mechanical Specifications

Operating Force	0.1N
Mounting Orientation	Vertical
Dimensions	30.3mm x 92mm x 30mm
Length	30.3mm
Width	92mm
Depth	30mm
Mechanical Life (Minimum)	15000000 Operations

Operation Environment Specifications

Maximum Operating Temperature	+70°C
Minimum Operating Temperature	-25°C
Ambient Temperature	-30°C to 80°C

Protection Category

IP Rating	IP65
Class of Protection Against Electric Shock	Class II

Approvals

Compliance/Certifications	UL, CSA, IMQ
Standards Met	CE, CSA, RU, UL



