


RoHS
Compliant



Physical Properties:

Monofilament Dia. (ASTM D-204)	: 0.01
Flammability Rating	: FAR 25, FMVSS 302
Recommended Cutting	: Hot Knife
Wall Thickness	: 0.025
Tensile Strength (ASTM D-2556)	: 85,000 psi
Abrasion Resistance (ASTM D4157)	: High
Tenacity (Gm/Denier) ASTM D-638	: 4.5
Specific Gravity (ASTM D-792)	: 1.38
Moisture Absorption (ASTM D-570)	: 0.08%
Smoke D-Max (ASTM E-662)	: 56
Toxicity Index (USN 713)	: 4.2

Typical Elongation (ASTM D-2256-80):

Break	: 15
3g/Denier	: 5

Hard Vacuum Data (ASTM E-595 at 10-5 torr):

TML	: 0.51
CVCM	: 0
WVR	: 0.1

Operating Temperatures:

Minimum Continuous	: -75°C [-103°F]
Maximum Continuous (Mil-I-23053)	: 125°C [257°F]
Melt (ASTM D-2117)	: 230°C [446°F]

Chemical Resistance (1 = No Effect, 2 = Little Effect, 3 = Affected)

Aromatic Solvents	: 2
Aliphatic Solvents	: 1
Chlorinated Solvents	: 3
Weak Bases	: 1
Salts	: 1
Strong Bases	: 2
Salt Water (O-S-1926)	: 1
Hydraulic Fluid (MIL-H-5606)	: 1
Lube Oil (MIL-L-7808)	: 1
De-Icing Fluid (MIL-A-8243)	: 1
Strong Acids	: 3
Strong Oxidants	: 2
Esters/Keytones	: 1
UV Light	: 1
Petroleum	: 1
Fungus (ASTM G-21)	: 1
Outgassing	: Med
Oxygen Index (ASTM D2863)	: 21
Halogen Free	: Yes

Part Number Table

Description	Nominal Size (Inch)	Colour	Expansion Range		Spool Length (Feet)	Part Number
			Min.	Max.		
PET (Polyethylene Terephthalate)	1/8	Black	3/32	1/4	100	8465-0228
	1/4	Black	1/8	7/16		8465-0229
		Clear				8465-0229-CLR
		Neon Red				8465-0229-NRED
		Neon Yellow				8465-0229-NYEL
		Neon Green				8465-0229-NGRN
		Neon Blue				8465-0229-NBLU
		Orange				8465-0229-ORG
		Purple				8465-0229-PUR
	3/8	Black	3/16	1/2	100	8465-0230
	1/2	Black	1/4	3/4	8465-0231	
		Clear			8465-0231-CLR	
		Neon Red			8465-0231-NRED	
		Neon Yellow			8465-0231-NYEL	
		Neon Green			8465-0231-NGRN	
		Neon Blue			8465-0231-NBLU	
		Orange			8465-0231-ORG	
		Purple			8465-0231-PUR	

Part Number Table

Description	Nominal Size (Inch)	Colour	Expansion Range		Spool Length (Feet)	Part Number		
			Min.	Max.				
PET (Polyethylene Terephthalate)	3/4	Black	1/2	1-1/4	50	8465-0232		
		Clear				8465-0232-CLR		
		Neon Red				8465-0232-NRED		
		Neon Yellow				8465-0232-NYEL		
		Neon Green				8465.0232-NGRN		
		Neon Blue				8465-0232-NBLU		
		Orange				8465-0232-ORG		
		Purple				8465-0232-PUR		
		Black				500	SPC23463	
	1-1/4	Black	3/4	1-3/4	50	8465-0233		
		Clear				8465-0233-CLR		
		Neon Red				8465-0233-NRED		
		Neon Yellow				8465-0233-NYEL		
		Neon Green				8465.0233-NGRN		
		Neon Blue				8465-0233-NBLU		
		Orange				8465-0233-ORG		
		Purple				8465-0233-PUR		
	1-1/2	Black	1	2-1/8	50	8465-0234		
					200	SPC14886		
	1-3/4				1-1/4	2-3/4	25	8465-0235
	2				1-1/2	3-1/2	25	8465-0236
	2-1/2				1-3/4	3-5/8	25	8465-0237

Shelf Life For Polyethylene Terephthalate

With or without FR additive

Shelf life for braided sleeving made with PET (Polyethylene Terephthalate) is indefinite under normal storage conditions.

Generally, "normal storage conditions" is a typical warehouse setting. The product should be:

-stored indoors

-where temperature doesn't exceed the minimum/maximum operating temperatures of

-103F/257F

-without constant exposure to chemicals such as aromatic solvents, chlorinated solvents, strong bases, strong acids, strong oxidants, which can affect polyester.

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro

Farnell.com/multicomp-pro

sg.element14.com/b/multicomp-pro