

**Rust Converter****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** Rust Converter  
Code-Nr. 111550

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

Technical Aerosols

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	

**Hazard Statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS05



GHS07



GHS08

### Signal word

Danger

### Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

### Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/eye protection.
P301 + P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

acetone, iso-butanol, Phenol, 4,4'-(1-methylethylidene)bis-polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenylene oxymethylene)] bis[oxirane], xylene

### 2.3. Other hazards



## Rust Converter

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Description

Mixture of active ingredients with propellant

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-63-0	200-661-7	propan-2-ol	2,5 < 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
67-64-1	200-662-2	acetone	10 < 25	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
71-36-3	200-751-6	butan-1-ol	2,5 < 10	Flam. Liq. 3, H226 / Acute Tox. 4, H302 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Eye Dam. 1, H318 / STOT SE 3, H336
115-10-6	204-065-8	dimethylether	25 < 50	Flam. Gas 1, H220 / Press. Gas
78-83-1	201-148-0	iso-butanol	0,1 < 1	Flam. Liq. 3, H226 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Eye Dam. 1, H318 / STOT SE 3, H336
107-98-2	203-539-1	1-methoxy-2-propanol	2,5 < 10	Flam. Liq. 3, H226 / STOT SE 3, H336 / Acute Tox. 4, H312
1330-20-7	215-535-7	xylene	10 < 25	Flam. Liq. 3, H226 / STOT RE 2, H373 / Asp. Tox. 1, H304 / Acute Tox. 4, H312, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / STOT SE 3, H335
25036-25-3		Phenol, 4,4'-(1-methylethyidene)bis-polymer with 2,2'-[(1-methylethyidene)bis(4,1-phenylene oxymethylene)] bis[oxirane]	1 < 2,5	Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin Sens. 1, H317

#### REACH

CAS No	Name	REACH registration number
67-63-0	propan-2-ol	01-2119457558-25
67-64-1	acetone	01-2119471330-49
71-36-3	butan-1-ol	01-2119484630-38
115-10-6	dimethylether	01-2119472128-37
78-83-1	iso-butanol	01-2119484609-23
107-98-2	1-methoxy-2-propanol	01-2119457435-35
1330-20-7	xylene	01-2119488216-32
25036-25-3	Phenol, 4,4'-(1-methylethyidene)bis-polymer with 2,2'-[(1-methylethyidene)bis(4,1-phenylene oxymethylene)] bis[oxirane]	not subject to registration

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.  
In the event of symptoms refer for medical treatment.



**In case of skin contact**

In case of contact with skin wash off immediately with soap and water.  
Consult a doctor if skin irritation persists.

**In case of eye contact**

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

**In case of ingestion**

Do not induce vomiting.  
Call for a doctor immediately.  
Rinse out mouth thoroughly with water.

**4.2. Most important symptoms and effects, both acute and delayed**

**Physician's information / possible symptoms**

vomiting  
Respiratory complaints  
Allergic symptoms  
Confusion

**Physician's information / possible dangers**

Causes serious eye damage.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Treatment (Advice to doctor)**

Keep under medical supervision for at least 48 hours.  
Symptoms may not occur until several hours.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam  
Dry powder  
Carbon dioxide  
sand  
Water spray jet

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Danger of bursting  
In case of fire formation of dangerous gases possible.  
Carbon monoxide (CO)  
Carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.  
Do not inhale explosion and/or combustion gases.

**Additional information**

Vapours are heavier than air and will spread on the ground.  
Cool endangered containers with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Allow to vaporise.

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

#### Additional Information

Sort out leaky cans and dispose according to regulations.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Provide good room ventilation even at ground level (vapours are heavier than air).

Take the usual precautions when handling with chemicals.

#### General protective measures

Avoid contact with eyes and skin

Do not inhale aerosols

Ensure sufficient ventilation.

#### Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

The heavy vapours may bridge a long distance to source of ignition.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Pay attention to general rules of internal fire prevention.

**Rust Converter****7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**Advice on storage compatibility**

Do not store together with animal feedstuffs.

Do not store together with food.

**Further information on storage conditions**

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Storage temperature may not exceed 40°C (=104°F).

Recommended storage temperature: room temperature.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
71-36-3	butan-1-ol	8 hours			EH40/2005
		Short-term	154	50	
115-10-6	Dimethyl ether	8 hours	766	400	EH40/2005
		Short-term	958	500	
107-98-2	1 -Methoxypropan-2-ol	8 hours	375	100	EH40/2005
		Short-term	560	150	
78-83-1	2-Methylpropan-1 -ol	8 hours	154	50	EH40/2005
		Short-term	231	75	
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	

**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
107-98-2	1-methoxy-2-propanol	8 hours	375	100	skin
		Short-term	568	150	
115-10-6	dimethylether	8 hours	1920	1000	
67-64-1	acetone	8 hours	1210	500	

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
107-98-2	1-methoxy-2-propanol	50,6 mg/kg	DNEL long-term dermal (systemic)	
		369 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
		553,5 mg/m <sup>3</sup>	DNEL acute inhalative (local)	
115-10-6	dimethylether	1894 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed 05.08.2019  
revision 11.11.2016 (GB) Version 1.0

**Rust Converter**

**DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
1330-20-7	xylene	289 mg/m <sup>3</sup>	DNEL acute inhalative (systemic)	
		289 mg/m <sup>3</sup>	DNEL acute inhalative (local)	
		289 mg/m <sup>3</sup>	DNEL acute inhalative (local)	
		180 mg/kg	DNEL long-term dermal (systemic)	
		77 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
67-63-0	propan-2-ol	888 mg/kg bw/day	DNEL long-term dermal (systemic)	
		500 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
67-64-1	acetone	186 mg/kg	DNEL long-term dermal (systemic)	
		1210 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
71-36-3	butan-1-ol	2420 mg/m <sup>3</sup>	DNEL acute inhalative (local)	
		55 mg/m <sup>3</sup>	DNEL long-term inhalative (local)	
		3,125 mg/kg bw/day	DNEL long-term oral (repeated)	
		310 mg/m <sup>3</sup>	DNEL long-term inhalative (local)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
1330-20-7	xylene	12,46 mg/kg	PNEC sediment, marine water	
		2,31 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, freshwater	
		12,46 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, marine water	
67-64-1	acetone	30,4 mg/kg	PNEC sediment, freshwater	
		10,6 mg/l	PNEC aquatic, freshwater	
		3,04 mg/kg	PNEC sediment, marine water	
71-36-3	butan-1-ol	1,06 mg/l	PNEC aquatic, marine water	
		0,0082 mg/l	PNEC aquatic, marine water	
		0,178 mg/kg	PNEC sediment, freshwater	
		0,082 mg/l	PNEC aquatic, freshwater	
		0,0178 mg/kg	PNEC sediment, marine water	

**Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls**

**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

**Rust Converter****Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

aerosol

**Colour**

brownish

**Odour**

solvent-like

**Odour threshold**

not determined

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	-24 °C				
<b>melting point</b>	not determined				
<b>Flash point</b>	not applicable				Aerosol
<b>Vapourisation rate</b>	not applicable				
<b>Flammable (solid)</b>	not applicable				
<b>Flammability (gas)</b>	not applicable				
<b>Ignition temperature</b>	235 °C				
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	1,1 Vol-%				
<b>Upper explosion limit</b>	20 Vol-%				
<b>Vapour pressure</b>	5200 hPa	20 °C			
<b>Relative density</b>	0,795 g/cm <sup>3</sup>				
<b>Bulk density</b>	not applicable				



**Rust Converter**

	Value	Temperature	at	Method	Remark
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					No or low immiscibility
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	not determined				
<b>Solvent content</b>	84,9 %				
<b>Water content</b>	4,4 %				
<b>Solids content</b>	10,5 %				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
<b>9.2. Other information</b>	No information available.				

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No hazardous reactions known.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 5000			ATE
<b>LD50 acute dermal</b>	> 5000			ATE
<b>LC50 acute inhalation</b>	> 30 ()			ATE
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	corrosive			
<b>Skin sensitization</b>	sensitizing			

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Chronic Toxicity</b>				-
<b>Mutagenicity</b>				No experimental information on genotoxicity in vitro available.
<b>Reproduction-Toxicity</b>				No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**Specific target organ toxicity (single exposure)**

May cause drowsiness or dizziness.

**Specific target organ toxicity (repeated exposure)**

May cause damage to organs, if longer exposed.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Experiences made from practice**

Sensitization through skin contact possible.

Risk of strong eye injuries.

Frequent persistent contact with the skin may cause skin irritation.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

**Rust Converter****SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
<b>Fish</b>	LC50 8,9 - 16,4 mg/l (96 h)	Pimephales promelas		CAS: 1330-20-7
<b>Daphnia</b>	NOEC 4,1 mg/l (21 d)	Daphnia magna		CAS: 71-36-3
<b>Algae</b>	LOEC 1000 mg/l (8 d)	Green algae		CAS: 67-63-0

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

Because of its consistency the product cannot be dispersed in the environment. Adverse ecological effects are therefore unlikely on the basis of current knowledge.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****General regulation**

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	1950	1950	1950
<b>14.2. UN proper shipping name</b>	AEROSOLS	AEROSOLS	Aerosols, flammable

**Rust Converter**

	ADR/RID	IMDG	IATA-DGR
<b>14.3. Transport hazard class(es)</b>	2.1	2	2.1

<b>14.4. Packing group</b>	-	-	-
----------------------------	---	---	---

<b>14.5. Environmental hazards</b>	No	No	No
------------------------------------	----	----	----

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 85 %

VOC value 676 g/L

**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL Code 4-5

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H312,	-?-
H332	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 11.11.2016 (GB) Version 1.0

**Rust Converter**

---

H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).