

Description	A premium modified alkyd transparent wood varnish.		
Recommended Use	As a decorative and protecting coatings for all types of new and previously painted wood surfaces.		
Application Areas	Interior and Exterior		
Characteristics	<ul style="list-style-type: none"> • Easy to apply • Quick Drying • Good Fungus Resistance • Good UV resistance • Excellent abrasion resistance • Excellent water resistance 		
Finish	Gloss & Matt		
Colour	Gloss Clear, Matt Clear, 9 colours (refer to colour chart)		
Technical Data	Specific Gravity (25°C)	: 0.92 ± 0.05	
	Flash Point	: 40°C	
Application Data	Application Method	: Brush, Spray or Roller	
	Thinner	: Urethane Oil Thinner	
	Dilution	: 0-10% by weight	
	Coverage	: Approx. 10 m ² /L	
	Drying Film Thickness	: Approx. 30 microns	
	Drying Time (30°C)	Surface Dry	: Approx. 30 min
		Hard Dry	: Approx. 1 h 30 min
Directions of Use	<ol style="list-style-type: none"> 1) Ensure surface is smooth, clean dry and free from grease and wax. 2) For previously painted surfaces remove all poorly adhering or Defective paint film. 3) Use sandpaper to sand all surfaces, 4) Clean off any excess dirt or sawdust. 5) Apply 2-3 coats of Winshield depending on the substrate. 6) Allow at least 4 hours drying between coats 		
Packaging	1 L, 5 L		
Storage	Should be tightly sealed and stored in cool, dry place.		