

Datasheet

## RS Pro Black Loop, 20mm x 5m

RS Stock No: **890-4168**



### Product Details

RS Pro adhesive-backed rubber loop strip in black colour, provides a strong instant bonding over a variety of surfaces including wood, paper, polyethylene, glass and plastic. It measures 20 mm x 5 m. This loop strip is suitable for use with rubber adhesive hook strips.

### Features and Benefits

- Strip provides a strong instant bonding
- Can be applied to a variety of surfaces including wood, paper, polyethylene, glass and plastic
- To be used in conjunction with Halco rubber adhesive hook strips - available separately
- Measures 20 mm x 5 m



ENGLISH

### Specifications:

Colour	Black
Format	Strip
Hook Type	Loop
Length	5 m
Width	20 mm



## Rubber Adhesive Strips

An adhesive backed premium hook & loop system comprising of a synthetic rubber and resin system adhesive coating to the back of the hook & loop tape, giving a strong instant bond.

**Adhesive colour:** Light Yellow

**Performance:** A strong instant bond

**Typical Application:** Immediate adhesion to a variety of surfaces including paper, wood, polythene, metal, glass, plastic etc. (excluding plasticised PVC)

<u>Item</u>	<u>Properties</u>	<u>Unit</u>	<u>Standard</u>		<u>Test method</u>
WDS4	Tape Test- Adhesive Holding Power	Minutes	646	686	PSTC-7
WDS4	Tape Test- Shear Adhesion Temperature Fail Level	°C	60	60	PSTC-7
WDS4	180°C Peeling Adhesion	Kg/cm	1.34	1.38	PSTC-1
WDS4	Shear Strength	Kg/cm <sup>2</sup>	0.85		CNS 12649 L3227
WDS4	Peel Strength	g/cm	200		CNS 12649 L3227
WDS4	Tearing Strength	Kg	2		ASTM D2261

Not recommended for direct exposure to sunlight & U.V.

**Application Guide:** To be avoided on surfaces of humidity, dust, oil etc.

Application and performance temperature from +5 to +40 degree C.

**Customer Attention:** The above points are suggestions and are not to be considered guarantees. All tapes should be tested in working conditions before long term use.