

FEATURES

- Shrink ratio: 3:1
- Semi-rigid, abrasion resistant
- Waterproof, moisture proof and UV resistant
- Excellent electrical insulation properties
- Compliance with RoHS and REACH environmental regulations
- Continuous operating temperature: -55°C~110°C
- Minimum shrink temperature: 80°C
- Full recovery temperature: Above 120°C

RS PRO

Medium Wall Adhesive Lined Heat Shrink Tubing

RS Stock No:

2269098

2269099

2269101

2269102

2269103

2269104

2269105

2269106



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Heat Shrink Tubing

Product Description

ATTRIBUTE 1

Medium wall heat shrinkable tubing is widely used in cable splice protection and metal pipe corrosion protection. The outer polyolefin and the inner thick layer of hot melt adhesive can provide long-term and reliable protection for objects in the outdoor environment.

General Specifications

Part Number	As supplied (mm)	After recovered (mm)		Standard Length (Meter)
	I.D.(min)	I.D.(max)	W.T.(min)	
2269098	12	3	2.0	1.22 meter/EA
2269099	16	5	2.2	1.22 meter/EA
2269101	19	5	2.2	1.22 meter/EA
2269102	33	8	2.6	1.22 meter/EA
2269103	55	16	2.7	1.22 meter/EA
2269104	75	22	3.0	1.22 meter/EA
2269105	95	25	3.0	1.22 meter/EA
2269106	115	34	3.0	1.22 meter/EA

Technical Data

Property	Test Method	Typical Value
Tensile strength	ASTM D638	≥12MPa
Elongation at break	ASTM D638	≥350%
Elongation at break after aging	ASTM D638 (150°C/168 hrs)	≥300%
Dielectric strength	ASTM D2671	≥10kV/mm
Volume resistivity	ASTM D876	≥10 ¹² Ω · cm

Additional Information

EAN	8000126233360
Custom Tariff Number	39173900

Approvals

Declarations	RoHS Reach
Hazardous Area Certification	ATEX / IECEx
Standards Met	VDE